



NORTH AMERICA
First Choice When Quality Matters



XT-Series Pumps

AR pumps are a combination of exceptional degree of technology and innovation, quality and reliability worthy of a leading brand on the market. The wide range includes many models which vary in terms of pressure, deliver, power and technical characteristics, to satisfy widely different market demands.

XT 1450 rpm N Version 24mm Solid Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XT8.14	2.11	2000	3	15	11	11
XT9.14	2.37	2000	3.3	18	8.4	11
XT11.14	2.9	2000	4	18	11	11

XTA 1750 rpm N Version 24mm Solid Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XTA2G15	2.11	2000	3	15	9.6	10
XTA2G22	2.11	2200	3	15	9.6	11
XTA3G16	3	1600	3	18	9.6	10
XTA3G19	3	1900	4	18	9.6	11
XTA3G22	3	2200	4.5	18	9.6	11

XTA 1750 rpm E Version 5/8" Hollow Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XTA0.5G10	0.5	1000	0.4	15	2.2	8.5
XTA1G15	1	1500	1	15	4.83	10
XTA2G15	2.11	1800	2.5	15	9.6	10
XTA2G22	2.11	2200	3	15	9.6	11
XTA3G16	3	1600	3	18	9.6	10
XTA3G19	3	1900	4	18	9.6	11
XTA3G22	3	2200	4.5	18	9.6	11
XTA4G15	4	1500	4	18	12.8	11

XTV 3400 rpm N Version 24mm Solid Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XTV3G22	3	2200	4.5	15	7.2	11