



**NORTH AMERICA**  
First Choice When Quality Matters



## XM/SXM-Series Pumps

AR pumps are a combination of exceptional degree of technology and innovation, quality and reliability worthy of a leading brand on the market. The wide range includes many models which vary in terms of pressure, deliver, power and technical characteristics, to satisfy widely different market demands.

### XM 1450 rpm N Version 24mm Solid Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XM11.17	2.9	2500	5	15	15.4	14
XM13.17	3.43	2500	5.5	18	12.4	14
XM15.15	3.96	2200	5.5	18	14.2	14

### XMA 1750 rpm N Version 24mm Solid Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XMA3G25	3	2500	5	15	13.2	14
XMA3.5G25	3.5	2500	5.5	15	15.4	14
XMA4G20	4	2000	5.5	18	13.2	14

### XMA 1750 rpm N Version 3/4" Solid Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XMA3.5G22	3.5	2200	5	15	15.4	14

### XMA 1750 rpm E Version 5/8" Hollow Shaft



Model	Max GPM	Max PSI	Power EBHP	Bore Dia mm	Stroke mm	Weight Lbs.
XMA2G15	2.11	1500	2	15	9.4	15
XMA2G22	2.11	2200	3	15	9.4	15
XMA2.5G18	2.5	1800	3	15	10.6	15
XMA3G18	3	1800	4	15	13.2	15