

# Triplex Plunger Pumps



## *XW 1450 RPM N VERSION* *24MM SOLID SHAFT*

MODEL	MAX. GPM	MAX. PSI	POWER EBHP	BORE DIA. MM	STROKE MM	WEIGHT LBS.	PRICE
XW15.15	3.96	2200	5.5	20	12.2	34	
XW15.20	3.96	2900	7.5	20	12.2	34	
XW15.30	3.96	4350	12.0	20	12.2	34	
XW21.20	5.55	2900	10.0	20	16.6	34	
XW21.25	5.55	3600	12.5	20	16.6	34	
XW21.28	5.55	4060	15.0	20	16.6	34	
XW26.12	6.87	1740	7.5	20	19.8	34	
XW26.15	6.87	2200	10.0	20	19.8	34	
XW26.20	6.87	2900	12.5	20	19.8	34	
XW26.23	6.87	3400	15.0	20	19.8	34	
XW30.10	7.92	1450	7.5	22	19.8	34	
XW30.15	7.92	2200	10.0	22	19.8	34	
XW30.20	7.92	2900	15.0	22	19.8	34	
XW30.25	7.92	3600	19.0	22	19.8	34	

## *XWA 1750 RPM N VERSION* *24MM SOLID SHAFT*

MODEL	MAX. GPM	MAX. PSI	POWER EBHP	BORE DIA. MM	STROKE MM	WEIGHT LBS.	PRICE
XWA4G20N	4.0	2000	5.5	20	10.0	34	
XWA4G30N	4.0	3000	7.5	20	10.0	34	
XWA4G40N	4.0	4000	11.0	20	13.8	34	
XWA5.5G22N	5.5	2200	7.5	20	13.8	34	
XWA5.5G30N	5.5	3000	10.0	20	13.8	34	
XWA5.5G40N	5.5	4000	14.0	20	13.8	34	
XWA7G22N	7.0	2200	10.0	20	17.2	34	
XWA7G32N	7.0	3200	14.0	20	17.2	34	
XWA7G35N	7.0	3500	15.0	20	17.2	34	
XWA7G40N	7.0	4000	17.0	20	17.2	34	
XWA8G19N	8.0	1900	10.0	20	19.8	34	
XWA8G29N	8.0	2900	15.0	20	19.8	34	
XWA8G35N	8.0	3500	18.0	20	19.8	34	
XWA9G16N	9.0	1600	10.0	22	19.8	34	
XWA9G24N	9.0	2400	15.0	22	19.8	34	