

XJV-E & XJW-E - Economy Axial Radial Drive Pumps



XJV-E 3400 RPM D VERSION - 3/4" WITH GAS ENGINE FLANGE (F7)

MODEL	MAX. GPM	MAX. PSI	POWER EBHP	BORE DIA. MM	STROKE MM	WEIGHT LBS.	PRICE
XJV-E2G15D-F7*	2.0	1450	2.0	15	4.8	11	
XJV-E2G20D-F7*	2.0	2000	2.8	15	4.8	11	
XJV-E2.5G15D-F7*	2.5	1450	2.5	15	5.8	11	
XJV-E2.5G20D-F7*	2.5	2000	3.4	15	5.8	11	
XJV-E2.5G22D-F7	2.5	2200	3.8	15	5.8	11	
XJV-E3G15D-F7*	3.0	1450	3.0	15	6.8	11	
XJV-E3G20D-F7*	3.0	2000	4.0	15	6.8	11	
XJV-E3G22D-F7*	3.0	2200	4.5	15	6.8	11	

OIL CAPACITY = 4.5 OZ MAXIMUM FLUID TEMPERATURE = 140° F

INLET THREAD = 1/2" M DISCHARGE THREAD = 3/8" M



XJW-E 3400 RPM D VERSION - 7/8" WITH VERTICAL GAS ENGINE FLANGE (F27)

XJW-E2G22D-F27	2.0	2200	3.0	15	4.8	11	
XJW-E2.5G22D-F27*	2.5	2200	3.7	15	5.8	11	
XJW-E3G22D-F27	3.0	2200	4.5	15	6.8	11	

OIL CAPACITY = 4.5 OZ MAXIMUM FLUID TEMPERATURE = 140° F

INLET THREAD = 1/2" M DISCHARGE THREAD = 3/8" M