

SJV & SJW & XJV - Super Duty Axial Radial Drive Pumps



SJV 3400 RPM D VERSION - 3/4"

WITH GAS ENGINE FLANGE (F7)

MODEL	MAX. GPM	MAX. PSI	POWER EBHP	BORE DIA. MM	STROKE MM	WEIGHT LBS.	PRICE
SJV2G25D-F7*	2.0	2500	3.5	15	4.8	11	
SJV2.5G24D-F7	2.5	2500	4.5	15	5.8	11	
SJV3G25D-F7	3.0	2500	5.0	15	6.8	11	

OIL CAPACITY = 4.5 oz MAXIMUM FLUID TEMPERATURE = 140° F INLET THREAD = 1/2" M DISCHARGE THREAD = 3/8" M



SJW 3400 RPM D VERSION - 7/8"

WITH VERTICAL GAS ENGINE FLANGE (F27)

SJW2G25D-F27*	2.0	2500	3.5	15	4.8	11	
SJW2.5G25D-F27	2.5	2500	4.5	15	5.8	11	
SJW3G25D-F27	3.0	2500	5.0	15	6.8	11	

OIL CAPACITY = 4.5 oz MAXIMUM FLUID TEMPERATURE = 140° F INLET THREAD = 1/2" M DISCHARGE THREAD = 3/8" M



XJV 3400 RPM E VERSION - 5/8"

WITH NEMA 56-C FLANGE (F8)

XJV2G15E-F8	2.0	1450	2.0	15	4.8	11	
XJV3G20E-F8	3.0	2000	4.0	15	6.8	11	

OIL CAPACITY = 4.5 oz MAXIMUM FLUID TEMPERATURE = 140° F INLET THREAD = 1/2" M DISCHARGE THREAD = 3/8" M