

# Temporary Berm Seals Off Spills From The Environment, Nearby Drains And Doorways




- Standard 10-foot sections can be cut to various lengths to meet custom needs.
- Unique, urethane material “weeps” into small cracks and crevices to seal off liquid flow.
- Spill Berm is non-absorbing and is easily cleaned for repeated use.
- Applications include:
  - Spill response
  - Temporary secondary containment
  - Sealing off of doorways during washdown operations
- Flexible Ultra-Spill Berm will bend and turn to form almost any shape while temporarily “bonding” to any smooth surface.
- **Helps comply with NPDES and SPCC.**

## ULTRA-SPILL BERM

Dimensions: 10' x 4" x 2 1/4" (3,048 mm x 102 mm x 58 mm)

Weight: 31 lbs. per unit (14 kg)

Material: Non-absorbing polyurethane



*Decide what shape or configuration is required and use optional Connectors and 90° Corners to complete the area.*

# Taller Spill Berm Helps Contain or Divert Larger Volume Spills

- Flexible polyurethane construction is non-absorbent and chemical resistant — easily cleans with soap and water for repeated uses.
- Built-in connectors allow multiple 5-foot units to be quickly and easily connected.
- **Helps comply with NPDES and SPCC.**

## ULTRA-SPILL BERM PLUS

Dimensions: 5' x 4" x 4 1/2" (1,524 mm x 102 mm x 114 mm)

Weight: 16 lbs. (7 kg) per unit

Material: Non-absorbing polyurethane

