

# HW

## Series Pumps

### 1450 RPM - 24mm Solid Keyed Shaft



- 1/2" FPT inlet, 3/8" FPT discharge
- Anodized, die-cast aluminum crankcase
- Solid Ceramic Plungers
- Stainless steel check valves
- Stainless steel piston guides
- Buna-textile V-packings
- Oversized bronze connecting rods
- Reversible crankcase for right or left hand mounting
- 24mm solid, keyed shaft

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
HW 4040 S	4.0	4000	1450	24mm Solid	18mm	20.0
HW 4540 S	4.5	4000	1450	24mm Solid	18mm	20.0

# HWS

## Series Pumps

### 1750 RPM - 24mm Solid Keyed Shaft



- 1/2" FPT inlet, 3/8" FPT discharge
- Anodized, die-cast aluminum crankcase
- Solid Ceramic Plungers
- Stainless steel check valves
- Stainless steel piston guides
- Buna-textile V-packings
- Oversized bronze connecting rods
- Reversible crankcase for right or left hand mounting
- 24mm solid, keyed shaft

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
HWS 4040 S	4.0	4000	1750	24mm Solid	18mm	20.0
HWS 5040 S	5.0	4000	1750	24mm Solid	18mm	20.0