

# TW

## Premium Series Pumps



# NEW



- Crankcase: Die-cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 5100 PSI
- One Piece, Solid Bronze Alloy Connection Rods
- Solid Shaft 24mm for Belt Drive, Gearbox or Flex Couplers
- Oil Cap: New Travel/Working Oil Cap
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life

# TWN

## 1000 RPM

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
TWN 7025 S	7.4	2500	1000	24mm	25mm	90.0
TWN 6036 S	5.7	3600	1000	24mm	22mm	90.0

# TW

## 1450 RPM

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
TW 11025 S	10.7	2200	1450	24mm	25mm	90.0
TW 10025 S	9.6	2500	1450	24mm	25mm	90.0
TW 4040 S	4.0	3500	1450	24mm	22mm	90.0
TW 5540 S	5.5	3600	1450	24mm	22mm	90.0
TW 7036 S	6.7	3600	1450	24mm	22mm	90.0
TW 8036 S	8.3	3600	1450	24mm	22mm	90.0
TW 4545 S	4.5	4500	1450	24mm	18mm	90.0
TW 5550 S	5.5	5100	1450	24mm	18mm	90.0

# TWS

## 1750 RPM

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
TWS 13020 S	12.9	2000	1750	24mm	25mm	90.0
TWS 10025 S	10.4	2500	1750	24mm	25mm	90.0
TWS 9030 S	9.0	3000	1750	24mm	22mm	90.0
TWS 8035 S	8.1	3500	1750	24mm	22mm	90.0
TWS 7040 S	6.7	4000	1750	24mm	18mm	90.0
TWS 5550 S	5.5	5100	1750	24mm	18mm	90.0