## LW, LWS, & LWD Series Pumps

1450 RPM

1750 RPM

3400 RPM

Forged bronze connecting rods with lifetime warranty

Hardened stainless steel piston guides

 High efficiency stainless steel check valves

 Abrasion Proof, Heat Resistant, Industrial Ceramic Plungers

- High quality buna-textile double sealing V-packings
- Solid or hollow shaft

Reversible crankshaft for easy right or left hand mounting

Die-cast, anodized aluminum crankshaft-Fin design for optimal operating temperature

Flange for direct mounting to gas engines or electric motors

High quality oversized ball bearings

Optimal oil bath for high speed operation



## LW

## **Series Pumps**

## 1450 RPM - 24mm Solid Shaft



- 1/2" FPT inlet, 3/8" FPT discharge
- Anodized, die-cast aluminum crankcase
- Solid Ceramic Plungers
- Stainless steel check valves & piston guides
- Buna-textile V-packings
- Reversible crankcase for right or left hand mounting
- 24mm solid, keyed shaft

MODEL#	<b>GPM</b>	PSI	RPM	SHAFT	<b>PISTON</b>	WT.
LW 2020 S	2.1	2000	1450	24mm Solid	15mm	13.4
LW 3020 S	3.0	2000	1450	24mm Solid	18mm	13.4
LW 3025 S	3.0	2500	1450	24mm Solid	18mm	13.4
LW 3525 S	3.5	2500	1450	24mm Solid	18mm	13.4