

LWD

Series Pumps

3400 RPM - 24mm Solid Shaft



- 1/2" FPT inlet, 3/8" FPT discharge
- Anodized, die-cast aluminum crankcase
- Solid Ceramic Plungers
- Stainless steel check valves & piston guides
- Buna-textile V-packings
- Reversible crankcase for right or left hand mounting
- 24mm solid, keyed shaft

| MODEL # | GPM | PSI | RPM | SHAFT | PISTON | WT. |
|--------------------------|-----|------|------|------------|--------|------|
| LWD 2010 SA [^] | 2.2 | 1000 | 3400 | 24mm Solid | 15mm | 10.4 |
| LWD 2020 S | 2.1 | 2000 | 3400 | 24mm Solid | 15mm | 13.4 |
| LWD 3020 S | 3.0 | 2000 | 3400 | 24mm Solid | 15mm | 13.4 |
| LWD 4020 S | 4.0 | 2000 | 3400 | 24mm Solid | 15mm | 13.4 |
| LWD 3522 S | 3.5 | 2200 | 3400 | 24mm Solid | 15mm | 13.4 |
| LWD 3025 S | 3.0 | 2500 | 3400 | 24mm Solid | 15mm | 13.4 |

LWD

Series Pumps

3400 RPM - NEMA 56C -5/8" or 3/4" Hollow Shaft



- 1/2" FPT inlet, 3/8" FPT discharge
- Anodized, die-cast aluminum crankcase
- Solid Ceramic Plungers
- Stainless steel check valves & piston guides
- Buna-textile V-packings
- Reversible crankcase for right or left hand mounting
- NEMA 56C electric motor flange with 5/8" or 3/4" hollow shaft

| MODEL # | GPM | PSI | RPM | SHAFT | PISTON | WT. |
|------------------------------------|-----|------|------|-------------|--------|------|
| LWD 2010 EA [^] | 2.2 | 1000 | 3400 | 5/8" Hollow | 15mm | 10.4 |
| LWD 2020 E | 2.1 | 2000 | 3400 | 5/8" Hollow | 15mm | 13.4 |
| LWD 3020 E | 3.0 | 2000 | 3400 | 5/8" Hollow | 15mm | 13.4 |
| LWD 3522 GE | 3.5 | 2200 | 3400 | 3/4" Hollow | 15mm | 13.4 |
| Pump with Built-In Unloader | | | | | | |
| LWD 2020 E-K | 2.1 | 2000 | 3400 | 5/8" Hollow | 15mm | 16.5 |