HEALTH AND SAFETY INFORMATION

Effects of Over Exposure:

- Ingestion: Damage to renal system may occur.
- Eyes: Causes severe eye irritation.
- Skin: Causes skin irritation.
- Inhalation: Causes respiratory tract irritation.

Emergency First Aid Procedures:

• Ingestion: Drink large quantities of water or milk and allow vomiting to occur. Examine victim for possible corrosive injury to mouth and throat and irrigate the areas with 1% Acetic Acid until alkali is neutralized. Seek medical attention immediately.

• Eyes: Remove contact lenses. Flush with copious amounts of water until all material is removed. If irritation develops or persists, seek medical attention immediately.

• Skin: Wash contacted area with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.

• Inhalation: Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulties persist seek medical attention.



READ & UNDERSTAND

the Material Safety Data Sheet prior to use. If no MSDS is present call: 1-800-346-4876

For Industrial or Professional Use Only. KEEP OUT OF REACH OF CHILDREN & ANIMALS

DECK & SHAKE BRIGHTENER

BRIGHTENS & REPAIRS UNTREATED WOOD RETURNS SURFACE TO "NEW" APPEARANCE

BLENDING INSTRUCTIONS

Deck & Shake Brightener should be mixed well using approximately 1/2 to 1 pound of product per 1 gallon of warm water. Deck & Shake Brightener will yield approximately 1 gallon of solution for every 1/2 to 1 pound of product.

USE INSTRUCTIONS

Always run a test pattern first and if acceptable spray the mix directly onto the surface. Rinsing is not required unless the surface is to be painted or stained shortly after application. This product can be reapplied 2 times at 24 hour intervals for maximum brightening. Do not allow the product to dry on glass or painted surfaces or come in contact with colored brick.

Deck & Shake Brightener neutralizes wood after an alkaline product has been used to clean it.

This Quality Product is Manufactured by:



A Division of Hi-Tech Jetting Technologies, Inc.