

Stop Spills From Going Down The Drain



- Reinforcing mesh is “sandwiched” between layers of polyurethane — increases durability and resistance to tearing.
- Unique, urethane construction allows the pad to deform and seal off most drains — temporarily “seals” to any smooth surface.
- A valuable addition to any emergency response plan, spill kit, SPCC or stormwater management program.
- Unlike some alternative products, BOTH sides will quickly seal drains — there is no specified “top” or “bottom.”



Optional Ultra-Drain Seal Wall Mount Units allow quick response to any spill — just “grab and go”!



ULTRA-DRAIN SEALS		ULTRA-DRAIN SEAL WALL MOUNT
Flexible, non-absorbing material with reinforced, tear-resistant mesh One unit per box, easily cuts to special shapes and sizes Resists oil, water and most aggressive chemicals, cleans with soap and water Prevents contaminants from entering drain Helps comply with SPCC Helps comply with NPDES	Square: 18" x 18" x 3/8" • 5 lbs. (458 mm x 458 mm x 10 mm • 2.5 kg) 24" x 24" x 3/8" • 8 lbs. (610 mm x 610 mm x 10 mm • 3.5 kg) 36" x 36" x 3/8" • 20 lbs. (915 mm x 915 mm x 10 mm • 9 kg) 42" x 42" x 3/8" • 23 lbs. (1067 mm x 1067 mm x 10 mm • 10.5 kg) 48" x 48" x 3/8" • 36 lbs. (1220 mm x 1220 mm x 10 mm • 17 kg) 54" x 54" x 3/8" • 41 lbs. (1372 mm x 1372 mm x 10 mm • 18.5 kg)	Fits 18" x 18", 24" x 24", 12" dia. and 20" dia. Drain Seals (458 mm x 458 mm, 610 mm x 610 mm, 305 mm dia. and 508 mm dia. Drain Seals) Fits 36" x 36" and 30" dia. Drain Seals (915 mm x 915 mm and 762 mm dia. Drain Seals)
	Circular: 12" dia. x 3/8" • 3 lbs. (305 mm dia. x 10 mm • 1.5 kg) 20" dia. x 3/8" • 6 lbs. (508 mm dia. x 10 mm • 3 kg) 30" dia. x 3/8" • 11 lbs. (762 mm dia. x 10 mm • 5 kg) 42" dia. x 3/8" • 19 lbs. (1067 mm dia. x 10 mm • 9 kg)	
	Rectangular: 18" x 58" x 3/8" • 16 lbs. (458 mm x 1474 mm x 10 mm • 7 kg) 36" x 58" x 3/8" • 26 lbs. (915 mm x 1474 mm x 10 mm • 12 kg)	