DUCT CLEANING SWIVEL

A duct cleaner is a high speed, high-pressure swivel that is designed to hold high-pressure nozzles at an angle the causes the swivel to spin. The swivel has a wire cage installed around it, which come in different sizes. These units are attached to a pressure washer using either a high-pressure hose or a lance. They are either lowered into, or pushed through ductwork. In addition to exhaust hood ductwork, these are commonly used to clean the inside walls of trash shoots, and sometimes air ducts. They hold two high-pressure nozzles, so the hole size normally used with one nozzle must be halved to maintain pressure. Any time restaurant or trash ductwork is being washed; the use of hot water is very beneficial. Try to size the cage of the swivel closely to the inner dimensions of the duct. The cage holds the swivel centered in the ductwork as it moves through. If it is too small, uneven cleaning will result. The swivel and cage assembly also tends to bounce around and bang against the ductwork if the cage is too small. On the other hand, a swivel with a cage that is bigger than the duct is no use at all. Because of this, the most popular sizes are 6" and 12".

Exhaust Hood Swivels. Non-Adjustable

MOSMATIC HOT WATER SWIVELS

• Fixed nozzle positioning ideally suited to be dropped down the exhaust hood.

To order the correct nozzles take the nozzle that you are presently using and divide it by the number of nozzles required by the Exhaust Hood Swivel you are ordering. For example: If you typically use a #6 nozzle such as a #1506 and you are buying a 3-Nozzle Swivel you will order 3 each #2 nozzles such as a #1502.



These swivels require 1/8" MEG Nozzles Sold Separately

PART#	DESCRIPTION	
2-NOZZLE HIGH SPEED		
1519	FIXED, 3", 2 NOZZLE	
1520	FIXED, 6", 2 NOZZLE	
1521	FIXED, 12", 2 NOZZLE	
1522	FIXED, 16", 2 NOZZLE	
1523	FIXED, 20", 2 NOZZLE	
1524	FIXED, 24", 2 NOZZLE	
3-NOZZLE HIGH SPEED		
1531	FIXED, 3", 3 NOZZLE	
1532	FIXED, 6", 3 NOZZLE	
1533	FIXED, 12", 3 NOZZLE	
1534	FIXED, 16", 3 NOZZLE	
1535	FIXED, 20", 3 NOZZLE	
1536	FIXED, 24", 3 NOZZLE	

Exhaust Hood Swivels, Adjustable

MOSMATIC HOT WATER SWIVELS

 Adjustable nozzle positioning to allow the swivel to pull itself.

To order the correct nozzles take the nozzle that you are presently using and divide it by the number of nozzles required by the Exhaust Hood Swivel you are ordering. For example: If you typically use a #6 nozzle such as a #1506 and you are buying a 3-Nozzle Swivel you will order 3 each #2 nozzles such as a #1502.



These swivels require 1/8" MEG Nozzles Sold Separately

PART #	DESCRIPTION	
2-NOZZLE HIGH SPEED		
1525	ADJUSTABLE, 3", 2 NOZZLE	
1526	ADJUSTABLE, 6", 2 NOZZLE	
1527	ADJUSTABLE, 12", 2 NOZZLE	
1528	ADJUSTABLE, 16", 2 NOZZLE	
1529	ADJUSTABLE, 20", 2 NOZZLE	
1530	ADJUSTABLE, 24", 2 NOZZLE	
3-NOZZLE HIGH SPEED		
1537	ADJUSTABLE, 3" 3 NOZZLE	
1538	ADJUSTABLE, 6" 3 NOZZLE	
1539	ADJUSTABLE, 12" 3 NOZZLE	
1540	ADJUSTABLE, 16" 3 NOZZLE	
1541	ADJUSTABLE, 20" 3 NOZZLE	
1542	ADJUSTABLE, 24" 3 NOZZLE	