

STAINLESS STEEL FRAMES GEARDRIVE



THE FIRST TRUE BUMPER-TO-BUMPER WARRANTY

- Die cast aluminum alloy crank case for protection again corrosion.
- Piston guides are heat treated stainless steel.
- Stainless steel check valves.
- Single piece, solid bronze alloy connecting rods.



Comet
TW5050S



General
T5050

STAINLESS STEEL



Back Side



GEARDRIVE

REQUIRES STAND-ALONE GAS TANK

| Model# | Engine | Pump | PSI | GPM | Weight |
|--------|----------------------------------|---------------|-------|-----|---------|
| | Honda Electric Start 20 HP GX620 | Comet TW5050S | 4,200 | 5.0 | 250 lbs |
| | Honda Electric Start 20 HP GX620 | General T5050 | 4,200 | 5.0 | 250 lbs |
| | Honda Electric Start 24 HP GX670 | Comet TW5050S | 5,000 | 5.0 | 250 lbs |
| | Honda Electric Start 24 HP GX670 | General T5050 | 5,000 | 5.0 | 250 lbs |

| Pic | Feature | Pic | Feature | Pic | Feature |
|-----|--------------------------------|-----|----------------------------------|-----|----------------------------|
| | • 21,000-25,000 Cleaning units | 4 | 13" Foam Filled Tires/Alum. Mags | 9 | 4 Quick-Connect Spray Tips |
| | • Honda 20-24 HP Gas Engine | 5 | Chemical Injector | | • Industrial Triplex Pump |
| 1 | Adjustable Unloader | 6 | 50' Steel Braided Rubber Hose | | • Stainless Steel Frame |
| 2 | Thermal Relief Valve (145°) | 7 | 5,000 PSI Spray Gun | | • Gearbox Drive |
| 3 | Safety Relief Valve | 8 | 36" Insulated Lance | | |



**HONDA
ENGINES**