



### PARTS LIST

Item	Part No.	Description	Kit No.	Qty.	Item	Part No.	Description	Kit No.	Qty.	Item	Part No.	Description	Kit No.	Qty.
1.	44.1206.41	Manifold		1	23.	44.0300.22	Connecting Rod		3	48.	96.7380.00	Washer		1
2.	99.3175.00	Screw		8	24.	90.3920.00	O-Ring		1	49.	96.7514.00	Washer		1
3.	96.7014.00	Washer		8	25.	44.1600.22	Rear Cover		1	50.	98.1966.00	Cap Screw		1
4.	90.3841.00	O-Ring	123	6	26.	99.1837.00	Screw		5	51.	90.2603.00	Seal, Low Pressure		3
5.	36.2003.66	Valve Seat	123	6	27.	90.3585.00	O-Ring		1	75.	90.0635.00	Retaining Ring		1
6.	36.2001.76	Valve	123	6	28.	98.2041.00	Cap Screw		1	76.	44.0221.65	Crankshaft (EZ4040G34)		1
7.	94.7376.00	Spring	123	6	29.	97.7340.00	Pin		3		44.0212.65	Crankshaft (EZ4035G34)		1
8.	36.2025.51	Valve Cage	123	6	30.	96.6967.00	Washer		3		44.0209.65	Crankshaft (EZ4030G34)		1
9.	90.3847.00	O-Ring	124	6	33.	44.0402.66	Plunger, 13 mm		3	77.	91.8568.00	Roller Bearing		1
10.	98.2226.00	Cap Screw	124	6	37.	50.2000.74	Rail		2	78.	90.4097.00	O-Ring		1
11.	36.7115.01	Valve Assembly	123	6	38.	96.7016.00	Washer		4	79.	99.2755.00	Screw, 5/16x1		4
12.	99.1807.00	Screw		4	39.	99.3037.00	Nut		4		99.3345.00	Screw, 3/8x1		4
13.	50.1500.74	Bearing Cover		1	40.	90.3612.00	O-Ring		3	80.	96.7020.00	Washer, Ø8 mm		4
14.	44.2118.01	Spacer		1	41.	44.0803.70	Packing Retainer		3		96.7104.00	Washer, Ø10 mm		4
15.	90.4097.00	O-Ring		1	42.	44.2162.70	Intermediate Ring		3	81.	10.0518.22	Gas Flange		1
16.	91.8328.00	Ball Bearing		1	43.	90.5076.00	Packing		3	82.	90.1690.00	Oil Seal		1
17.	90.1614.00	Oil Seal	23	3	44.	90.2602.00	Packing		3	83.	96.6938.00	Washer		4
18.	44.0100.22	Crankcase		1	45.	44.1002.51	Head Ring		3	84.	99.1912.00	Screw		4
19.	98.2103.00	Oil Dip Stick		1	46.	98.2100.00	Cap Screw		1					
22.	44.0501.66	Piston Guide		3	47.	98.2176.00	Cap Screw		1					

### REPAIR KITS

KIT NO.	23	123	124		
ITEM NO'S INCLUDED IN KIT	17	4, 5, 6, 7, 8, (11)	9, 10	43, 44, 51	40, 41, 42, 43, 44, 45, 51
NUMBER OF ASSEMBLIES IN KIT	3	6	6	3	1
NUMBER OF CYLINDERS KIT WILL SERVICE	3	3	3	3	1

### TORQUE SPECS\*

Position	Ft.-lbs.	N-M
2	14.7	20
10	73.7	100
12	7.3	10
26	7.3	10
28	14.7	20
46	29.4	40
47	29.4	40
50	9.6	13
79	14.7	20
84	7.3	10

\*Decrease torque by 20% if threads are lubricated.

