

Collapsible Wall Model

Economical Design Offers Cost Savings And Secure Containment



- The Collapsible Wall Model Containment Berm features rugged PVC sidewall assemblies for sidewall support. Simply swivel the “feet” of the PVC supports to lower or raise the sidewalls in just seconds!
- Custom sizes available.
- Meets SPCC and EPA Container Storage Regulations 40 CFR 264.175.



Simply swivel the “feet” of the PVC supports to lower the sidewall. Vehicles and equipment can then roll over the top of the collapsed wall for convenient entry and exit.

ULTRA-CONTAINMENT BERMS, COLLAPSIBLE WALL MODEL

Part#	Dimensions	Weight	Containment Capacity
	4' x 6' x 1' (1.2 m x 1.8 m x .3 m)	43 lbs. (19.5 kg)	179 gallons (678 L)
	6' x 6' x 1' (1.8 m x 1.8 m x .3 m)	46 lbs. (21 kg)	269 gallons (1,018 L)
	10' x 10' x 1' (3.0 m x 3.0 m x .3 m)	70 lbs. (32 kg)	748 gallons (2,831 L)
	12' x 60' x 1' (3.7 m x 18.3 m x .3 m)	323 lbs. (147 kg)	5,385 gallons (20,382 L)
	15' x 50' x 1' (4.6 m x 15.2 m x .3 m)	319 lbs. (145 kg)	5,610 gallons (21,234 L)
	15' x 66' x 1' (4.6 m x 20.1 m x .3 m)	420 lbs. (191 kg)	7,405 gallons (28,028 L)

Material of Construction: Copolymer 2000™, an ethylene copolymer, is standard. Copolymer 3000™, XR5, polyurethane and other materials are also available on a custom basis.
Options: Ground Tarps, Track Belts, Self Bailer, see page 31.



Rugged design easily contains small and large spills.