

## HOUSE WASH SPECIALTY PRODUCTS

**RESTORE****Simply Put - Awesome!  
Brings Old Wood Back to NEW**

Cedar Shakes & Unpainted Wood Surfaces such as Decks - Stripping Antique Furniture - Cleaning Tile Grout - Laundry Presoak & Bleach Replacement - Carpet Cleaning ... *you just won't find anything better than RESTORE!*

For Cedar Shakes and unpainted Wood Decks simply spray RESTORE on, wait 20 to 30 minutes, and rinse off. You will not believe your eyes! No more harsh bleach or surface and vegetation aggressive chemicals. Totally removes black mold and mildew build-up on shakes, regardless of how long it has been there.

RESTORE works by means of oxygenation and should not be mixed with water until the operator is ready to perform the job. Once RESTORE is in solution, the operator will have approximately 1-2 hours before the product has exhausted itself. Mix up enough so that you will be able to get the product on the surface within this time. Mix approximately 1/2 to 1 pound of RESTORE into 1 gallon of water and stir several turns. Complete solubility is not necessary since RESTORE will go into solution on it's own through the oxygenation process. Using a ShurFlo Pump place the pick-up line in the solution and spray product directly onto the surface. When product has removed pollutant, rinse with low pressure, 500 - 1000 PSI is all that is required. When using this product on pressure treated wood we recommend the 1/2 lb to 1 gallon of water ratio and rinsing with no more than 500 PSI. Higher dilutions and pressures will cause the surface to 'fuzz' up. When this happens it is generally a temporary situation that will correct itself in a couple of days. Do not use a pump-up sprayer to apply Restore since this product builds pressure when added to water and will over pressurize the sprayer which could result in an injury should the sprayer erupt.

This product will provide unbelievable results. You will be able to produce twice the results in 1/3 the time and with little to no mess. You'll never use harsh chlorine cleaners or solvent based strippers again.

5 Gallon Kit order **#RES5 \$50.00**  
55 Gallon Kit order **#RES55 \$97.00**

**SHIPPING INCLUDED**

**FIBER-X****The Purest Form of Oxygenated Cleaners  
& the only one with d'Limonene Solvents**

We are widely regarded as one of the leading global experts in the development and implementation of Green cleaning solutions and the invention Fiber-X, our latest wood rejuvenator, is a good example why most experts turn to EnviroSpec to help them with their toughest cleaning projects.

**Fiber-X** is a blend of oxygenators, orange peel solvents and cross-linked surfactants that break the degenerative cycle of drying & decaying wood fibers that begins when environmental factors come into play. When used as directed Fiber-X breaks this cycle by allowing the wood to breath more efficiently. The orange peel solvents help to penetrate and eliminate any existing wood destroying bacteria by weakening it's cell wall. When the cell wall is weakened or disrupted, it can no longer function. This forces the cell to burst due to osmotic effects (water rushing into the cell). At this point wood fibers can recapture their shape while continuing to exist in a harsh outdoor environment.

For best results place 1/2 to 3/4 pound of product into a clean 5 gallon pail filled with slightly warm water. Pour in the product and stir 8-10 times. At this point approximately 80% of the powder will still be at the bottom of the pail. Apply by placing the chemical pick-up line from a 12V or 115V SHURflo or Flojet pump at the bottom of the pail and begin to drench the wood surface. By the time you have completely drained the pail all of the product will have been solubilized through its own oxygenation process. Allow to stand for approximately 15-20 minutes and rinse.

In some cases, especially with pressure treated wood, the surface will 'fuzz'. This will normally return to its natural state in a few days. Occasionally a light sanding may be required. It is because of this that we recommend a 1/2 pound per gallon of warm water for pressure treated wood.

5 Gallon Kit order **#FIB5 \$50.00**  
55 Gallon Kit order **#FIB55 \$99.60**

**SHIPPING INCLUDED**

**DECK & SHAKE BRIGHTENER****High pH 'detergent beds' especially sodium or potassium hydroxide, shorten the life of wood.  
DECKS MUST BE NEUTRALIZED AFTER CLEANING!**

DSB (Deck & Shake Brightener) is a product that must be applied to a wooden deck in order to neutralize and brighten the wood after being cleaned.

Quite often contractors who are just starting out in the deck cleaning business will use harsh sodium or potassium hydroxide base cleaners to perform this service. Although the hydroxide family of products are extremely effective in the drain cleaning and exhaust hood cleaning industries they are not recommended for wood cleaning. When used they immediately start breaking down wood fibers.

The ideal deck cleaning system would be cleaning the deck first with our product Restore or Fiber-X and then applying a coat of Deck & Shake Brightener.

The Restore and Fiber-X will be sprayed on and allowed to sit for approximately 20 minutes. Reapply if necessary. Rinse and apply a coat of DSB and allow to stand for another 20 minutes.

The DSB process will return the wood to a neutral pH as well as begin a brightening process.

5-Gallon Kit order **#DSB5 \$50.00**  
55-Gallon Kit order **#DSB55 \$86.00**

**SHIPPING INCLUDED**

**Professionals are expensive but not near as expensive as an amateur.**