

HEALTH AND SAFETY INFORMATION

Effects of Over Exposure:

- **Ingestion:** Damage to renal system may occur.
- **Eyes:** Causes severe eye irritation.
- **Skin:** Causes skin irritation.
- **Inhalation:** Causes respiratory tract irritation.

Emergency First Aid Procedures:

• **Ingestion:** Drink large quantities of water or milk and allow vomiting to occur. Examine victim for possible corrosive injury to mouth and throat and irrigate the areas with 1% Acetic Acid until alkali is neutralized. Seek medical attention immediately.

• **Eyes:** Remove contact lenses. Flush with copious amounts of water until all material is removed. If irritation develops or persists, seek medical attention immediately.

• **Skin:** Wash contacted area with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.

• **Inhalation:** Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulties persist seek medical attention.

IN CASE OF EMERGENCY CALL

CHEMTREC
1-800-424-9300

READ & UNDERSTAND

the Material Safety Data Sheet prior to use.
If no MSDS is present call: 1-800-346-4876

For Industrial or Professional Use Only.
KEEP OUT OF REACH OF CHILDREN & ANIMALS

FINAL PHAZE



CITRUS BASE ROOF SEALER THAT KILLS THE MILDEW ROOT BED AND RETARDS MILDEW GROWTH UP TO 18 MONTHS.

MIXING INSTRUCTIONS

1 gallon of FINAL PHAZE will make 5 gallons of concentrate. Further dilution required.

APPLICATION

Apply using an Allison Super Suds Sucker downstream injector. Part number: 1964

Work in small sections. For best results split the roof in quarters. This is a super concentrate even through an injector so apply just enough to get the roof good and wet. It is best not to let the product dry before you perform a quick 'dusting' light rinse.

If you are using a SHURflo or EVERflo pump pre-mix 1 gallon of product with 25 gallons of water. Spray on and lightly rinse.

DWELL TIME

Final Phaze activates and locks into the surface upon contact. Large amounts are not required.

FOLLOW-UP COAT

After one year it is recommended that you re-contact the customer and schedule a follow-up service.

Note: as is the case with all cleaning and sealing products it is always safe to perform a test pattern first to make sure that the product is compatible with the surface. Often times you will be following a contractor who, in the past, has used cleaners that may react adversely with sealers and other cleaners.

This Quality Product is Manufactured by:

ENVIROSPEC

A Division of Hi-Tech Jetting Technologies, Inc.