



■ T Series 47, Triplex Plunger Pump, Solid Shaft – 316 Stainless Steel Manifold. Heavy duty tapered roller bearings and over sized connecting rods for maximum life.

Max. Inlet Pressure: 125 PSI Max. Fluid Temperature: 165° F Inlet Port Thread: 1/2" - 14 BSP-F

Discharge Port Thread: 3/8" - 19 BSP-F Shaft Diameter: .945 in./24 mm

Pump Dimensions: 12.25" x 9.2" x 6.9" Max. Inlet Vacuum: 9 ft. water (7.9 in. Hg)

Crankcase Oil Capacity: 40.6 oz.

	GPM	PSI	RPM	BORE	STROKE	HP	SHP WGHT
TS2012SS	4.0 GPM	2200 PSI	1450 RPM	.787 in./20 mm	.472 in./12 mm	6.0 EBHP	31.0 lbs.
TS2012SS	4.75 GPM	2200 PSI	1750 RPM	.787 in./20 mm	.472 in./12 mm	7.2 EBHP	31.0 lbs.
TS2212SS	4.75 GPM	2200 PSI	1450 RPM	.866 in./22 mm	.472 in./12 mm	7.2 EBHP	31.0 lbs.
TS2016SS	5.55 GPM	2200 PSI	1450 RPM	.787 in./20 mm	.630 in./16 mm	8.4 EBHP	31.0 lbs.
TS2212SS	5.55 GPM	2200 PSI	1750 RPM	.866 in./22 mm	.472 in./12 mm	8.4 EBHP	31.0 lbs.