



■ T Series 47, Triplex Plunger Pump, Solid Shaft – Forged brass manifold with an exclusive lifetime warranty. Heavy duty tapered roller bearings and over sized connecting rods for maximum life.  
**Max. Inlet Pressure: 125 PSI Max. Fluid Temperature: 165° F Inlet Port Thread: 1/2" - 14 BSP-F**  
**Discharge Port Thread: 3/8" - 19 BSP-F Shaft Diameter: .945 in./24 mm**  
**Pump Dimensions: 12.2" x 9.2" x 6.9" Max. Inlet Vacuum: 9 ft. water (7.9 in. Hg)**  
**Crankcase Oil Capacity: 33.8 oz.**

	GPM	PSI	RPM	BORE	STROKE	HP
TS1331	3.5 GPM	2100 PSI	1450 RPM	.787 in./20 mm	.394 in./10 mm	5.0 EBHP
TS1011	4.0 GPM	2000 PSI	1450 RPM	.787 in./20 mm	.472 in./12 mm	5.5 EBHP
TS1331	4.0 GPM	2000 PSI	1750 RPM	.787 in./20 mm	.394 in./10 mm	5.5 EBHP
T1011	4.5 GPM	2000 PSI	1125 RPM	.787 in./20 mm	.630 in./16 mm	6.1 EBHP
TS1011	4.75 GPM	1500 PSI	1750 RPM	.787 in./20 mm	.472 in./12 mm	5.5 EBHP
TS921	4.75 GPM	1800 PSI	1450 RPM	.866 in./22 mm	.472 in./12 mm	5.9 EBHP
T921	5.0 GPM	1700 PSI	1050 RPM	.866 in./22 mm	.630 in./16 mm	5.8 EBHP
T1011	5.6 GPM	1500 PSI	1450 RPM	.787 in./20 mm	.630 in./16 mm	5.5 EBHP



■ T Series 47, Triplex Plunger Pump, Solid Shaft – Forged brass manifold with an exclusive lifetime warranty. Heavy duty tapered roller bearings and over sized connecting rods for maximum life.  
**Max. Inlet Pressure: 125 PSI Max. Fluid Temperature: 165° F Inlet Port Thread: 1/2" - 14 BSP-F**  
**Discharge Port Thread: 3/8" - 19 BSP-F Shaft Diameter: .945 in./24 mm**  
**Pump Dimensions: 12.25" x 9.2" x 6.9" Max. Inlet Vacuum: 9 ft. water (7.9 in. Hg)**  
**Crankcase Oil Capacity: 40.6 oz.**

	GPM	PSI	RPM	BORE	STROKE	HP
TS1711	3.5 GPM	2700 PSI	1450 RPM	.787 in./20 mm	.394 in./10 mm	7.2 EBHP
T9211	4.0 GPM	3000 PSI	1750 RPM	.787 in./20 mm	.394 in./10 mm	8.2 EBHP
TS1511	4.0 GPM	3500 PSI	1450 RPM	.787 in./20 mm	.472 in./12 mm	9.6 EBHP
TS2011	4.0 GPM	3500 PSI	1450 RPM	.787 in./20 mm	.472 in./12 mm	9.6 EBHP
TS2021	4.5 GPM	3500 PSI	1125 RPM	.787 in./20 mm	.630 in./16 mm	10.8 EBHP
TS1021	4.5 GPM	3000 PSI	1125 RPM	.787 in./20 mm	.630 in./16 mm	6.5 EBHP
TS1321	4.75 GPM	2100 PSI	1450 RPM	.866 in./22 mm	.472 in./12 mm	6.8 EBHP
TS1621	4.75 GPM	2500 PSI	1450 RPM	.866 in./22 mm	.472 in./12 mm	8.2 EBHP
TS2011	4.75 GPM	2300 PSI	1750 RPM	.787 in./20 mm	.394 in./10 mm	7.5 EBHP
T1621	5.0 GPM	2500 PSI	1050 RPM	.866 in./22 mm	.630 in./16 mm	8.6 EBHP
T1321	5.5 GPM	2100 PSI	1150 RPM	.866 in./22 mm	.630 in./16 mm	7.9 EBHP
TS2021	5.6 GPM	3500 PSI	1450 RPM	.787 in./20 mm	.630 in./16 mm	13.5 EBHP
TS1021	5.6 GPM	1700 PSI	1450 RPM	.787 in./20 mm	.630 in./16 mm	6.5 EBHP



■ T Series 47, Triplex Plunger Pump, Solid Shaft – Forged brass manifold with an exclusive lifetime warranty. Heavy duty tapered roller bearings and over sized connecting rods for maximum life.  
**Max. Inlet Pressure: 125 PSI Max. Fluid Temperature: 165° F Inlet Port Thread: 1/2" - 14 BSP-F**  
**Discharge Port Thread: 3/8" - 19 BSP-F Shaft Diameter: .945 in./24 mm**  
**Pump Dimensions: 12.6" x 9.2" x 6.9" Max. Inlet Vacuum: 9 ft. water (7.9 in. Hg)**  
**Crankcase Oil Capacity: 40.6 oz.**

	GPM	PSI	RPM	BORE	STROKE	HP
T9281	4.0 GPM	4000 PSI	1750 RPM	.630 in./16 mm	.630 in./16 mm	11.0 EBHP



■ T Series 47, Triplex Plunger Pump, Solid Shaft – Forged brass manifold with an exclusive lifetime warranty. Unique "in-line" valve system for easy access and durability, proven crankcase and bearing design.

**Max. Inlet Pressure: 125 PSI Max. Fluid Temperature: 165° F Inlet Port Thread: 1/2" - 14 BSP-F**  
**Discharge Port Thread: 3/8" - 19 BSP-F Shaft Diameter: .945 in./24 mm**  
**Pump Dimensions: 14.2" x 9.2" x 6.9" Max. Inlet Vacuum: 30 PSI**  
**Crankcase Oil Capacity: 40.6 oz.**

	GPM	PSI	RPM	BORE	STROKE	HP
T5050	5.0 GPM	5000 PSI	1845 RPM	.630 in./16 mm	.748 in./19 mm	17.2 EBHP