

Copyright @2008 Idrobase. All rights reserved.

Car line of accessories

Innovative approaches by thinking outside of the box

The way we meet the needs of the customer has enabled us to innovate and to improve on a poor product, so that finally it meets the requirements of the user; more performance, more useful, safer and more comfortable than the products of the past.

The only thing that will remain unchanged with respect to the products of yesterday is its selling price, which will be of great benefit to our distributors and clients, and of great concern to our competitors.







The reason for a new line of high pressure washer accessories

It is well known that through the gun and the lance, the pressure washer can transmit strong vibrations from the pump to the user.

The strength generated by the pressure

The strength generated by the pressure and force of the water jet that exits the lance through the nozzle, together with the shocks caused by the repeated opening and closing of the trigger of the gun can cause stress that can fatigue the hands, forearms and also the shoulders of the user. In some cases this can result in "tennis elbow".

This is a genuine and serious occupational hazard that affects users of high pressure washers.

Club dei Riparatori of Idrobase, with its new line of accessories transforms what was previously tiring and stressful cleaning into a simple and relaxing job.

CdR® 90 and 990 are professional guns.

The ergonomic grip enables the gun to be held comfortably and securely, and distributes the force applied to the gun by the water jet evenly through the hand. The surface of the gun that is in contact with the palm was specifically designed in soft rubber to cushion the vibrations transmitted by the pump.

The inclination of the gun connected to the lance is perfectly balanced, reducing the force imparted by the water jet.



CdR® 90 spray guns

Max: 280 bar-4050 psi, 25 l/min-6.60 USGpm, 150 °C-300 °F

Code	Inlet	Outlet	Weight gr. <i>oz.</i>	
CDR.7400	G 3/8" F	G 1/4" F	650	22.8
CDR.7402	G 3/8" M	G 1/4" F	670	23.5
CDR.7403	M 22x1,5 M	G 1/4" F	685	24.0



CdR® 990 spray guns

Max: 345 bar-*5000 psi*, 40 l/min-*10.50 USGpm*, 150 °C-*300 °F*

Code	Inlet	Outlet	Weight gr. <i>oz.</i>	
CDR.7404	G 3/8" F	G 1/4" F	650	22.8
CDR.7406	G 3/8" M	G 1/4" F	670	23.5
CDR.7407	M 22x1,5 M	G 1/4" F	670	23.5
CDR.7408	M 22x1,5 M	M 22x1,5 M	685	24.0





CdR® 80 professional moulded handle lances

will offer the user the following advantages over the previous, old models:

- A rubber casing covers the space between the gun and lance combining them into one. This unique solution, the only one in the world, protects the operator from potential electric shocks and therefore satisfying health and safety regulations.
- *The ergonomic handle*, as well as making the lance enjoyable to use, makes it easy to hold and reduces fatigue that can result after heavy, continuous use. Even under heavy usage the lance does not tire the arms and shoulders.
- *The bend* is designed to perfectly balance the strength of the water jet against the weight of the gun. The result is a lance that the operator can use with just one hand.
- *The special nozzle cover* protects the nozzle and eliminates the possibility of scratching the surface being cleaned and gives the operator a useful guideline to follow while washing.

CdR® 80 moulded handle lance with bend

Max: 280 bar-4050 psi, 40 l/min-10.50 USGpm, 150 °C-300 °F

ſ		Ler	ngth	0-4-1		Weight	
	Code	mm	inches	Inlet	Outlet	gr.	0Z.
Ī	ZX.7114	500	20"	G 1/4" M	1/4" NPT-F	390	13.7
Ī	ZX.7115	700	28"	G 1/4" M	1/4" NPT-F	480	16.8
ĺ	ZX.7116	900	36"	G 1/4" M	1/4" NPT-F	580	20.3
Ī	ZX.7117	1200	47"	G 1/4" M	1/4" NPT-F	830	29.1
ľ	ZX.7118	1500	59"	G 1/4" M	1/4" NPT-F	1040	36.4
I	ZX.7119	1700	67"	G 1/4" M	1/4" NPT-F	1140	39.9
ĺ	ZX.7120	2000	79"	G 1/4" M	1/4" NPT-F	1240	43.4

Made of chromed steel

CdR® 80 moulded handle straight lance

Max: 280 bar-4050 psi, 40 l/min-10.50 USGpm, 150 °C-300 °F

Code	Ler mm	ngth inches	Inlet	Outlet	Wei gr.	ight <i>oz.</i>
ZX.7127	700	28"	G 1/4" M	1/4" NPT-F	480	16.8
ZX.7128	900	36"	G 1/4" M	1/4" NPT-F	580	20.3
ZX.7129	1200	47"	G 1/4" M	1/4" NPT-F	830	29.1

Made of chromed steel

CdR® 80 moulded blue handle lance with bend

Max: 280 bar-4050 psi, 40 l/min-10.50 USGpm, 150 °C-300 °F

Code	Lei mm	ngth inches	Inlet	Outlet	Wei gr.	ight <i>oz.</i>
ZX.7124	700	28"	G 1/4" M	1/4" NPT-F	500	17.5
ZX.7125	900	36"	G 1/4" M	1/4" NPT-F	590	20.7
ZX.7126	1200	47"	G 1/4" M	1/4" NPT-F	880	30.8

Made of stainless steel AISI 304



CdR® 55 professional vented handle lances

will offer the user the following advantages over the previous, old models:

- **Soft handle** provides thermal insulation and a secure connection which allows the handle to be housed securely next to the gun, thus combining the two components into one.
- *The bend* is designed to perfectly balance the strength of the water jet against the weight of the gun. The result is a lance that feels more like a feather in the hands of the operator and can be used effortlessly even with just one hand.
- *The special nozzle cover* protects the nozzle and eliminates the possibility of scratching the surface being cleaned and gives the operator a useful guideline to follow while washing.

CdR® 55 vented handle lances, with bend Max: 280 bar-4050 PSI, 40 I/min-10.50 USGpm, 150 °C-300 °F

ſ	Code	Ler mm	inches	Inlet	Outlet	Wei gr.	ight <i>oz.</i>
ŀ	ZX.7106	500	20"	G 1/4" M	1/4" NPT-F	475	16.7
	ZX.7107	700	28"	G 1/4" M	1/4" NPT-F	550	19.3
ľ	ZX.7108	900	36"	G 1/4" M	1/4" NPT-F	630	22.1
	ZX.7109	1200	47"	G 1/4" M	1/4" NPT-F	970	34.0
	ZX.7110	1500	59"	G 1/4" M	1/4" NPT-F	1090	38.2
	ZX.7111	1700	67"	G 1/4" M	1/4" NPT-F	1170	38.2
	ZX.7112	2000	79"	G 1/4" M	1/4" NPT-F	1295	45.4

Made of chromed steel





The spare parts branded "CdR®" exclusively refer to products by Club dei Riparatori® by IDROBASE®



Max: 280 bar-4050 psi 40 I/min-10.50 USGpm 150 °C-300 °F

Code	Ler	igth	Inlet	Outlet	Wei	ight
Oode	mm	inches	IIIICt	Outlet	gr.	OZ.
ZX.1071-M18	500	20"	M 22x1,5 F	M 18x1 M	670	23.5
ZX.1072-M18	700	28"	M 22x1,5 F	M 18x1 M	750	26.3
ZX.1073-M18	900	36"	M 22x1,5 F	M 18x1 M	830	29.1
ZX.1074-M18	1200	47"	M 22x1,5 F	M 18x1 M	1170	41.0
ZX.1075-M18	1500	59"	M 22x1,5 F	M 18x1 M	1290	45.2
ZX.1076-M18	1700	67"	M 22x1,5 F	M 18x1 M	1370	48.0
ZX.1077-M18	2000	79"	M 22x1,5 F	M 18x1 M	1490	52.2
			,			

Made of chromed steel

ZX.7019

Brass adapter fitting Kärcher, inlet M 18x1 F, outlet G 1/4" M.

It is ideal to mount inlet G 1/4" F nozzles on lances fitting Kärcher with con-nection M 18x1 M.



gr. 30 oz. 1.8 CDR.7023

Tip retainer, M 18x1 F



gr. 30 oz. 1.1

CDR.7024 Brass nozzle holder, G 1/4" F-M 18x1 M



gr. 30 oz. 1.1 ZX.0154

Set O-Ring for brass nozzle holder



gr. 20 oz. 0.9

quantity 1x100

Spray guns
- CdR® 90 and 990 with extension

The spare parts branded "CdR®" exclusively refer to products by Club dei Riparatori® by IDROBASE®



Co	do	Inlet	Outlet	Weight		
COL	ue	IIIIet	Outlet	gr.	OZ.	
ZX.7	100	G 3/8" F	M 22x1,5 F	1090	38.2	
ZX.7	135	G 3/8" M	M 22x1,5 F	1110	38.9	
ZX.7	102	M 22x1,5 M	M 22x1,5 F	1110	38.9	

CdR® 90 spray guns with extension

Max: 280 bar-4050 psi 25 I/min-6.60 USGpm 150 °C-300 °F



Code	Inlet	Outlet	Weig gr.	ght <i>oz.</i>
ZX.7103	G 3/8" F	M 22x1,5 F	1090	38.2
ZX.7136	G 3/8" M	M 22x1,5 F	1110	38.9
ZX.7105	M 22x1,5 M	M 22x1,5 F	1110	38.9

CdR® 990 spray guns with extension

Max:

345 bar-5000 psi 40 I/min-10.50 USGpm 150 °C-300 °F



- Extension and nozzle holders

The spare parts branded "CdR®" exclusively refer to products by Club dei Riparatori® by IDROBASE®

CDR.7409

CdR 60 vented handle extension for gun, 380 mm-15".

Made of chromed steel, inlet G 1/4" M,

Made of zinced steel,

inlet G 1/4" F.

outlet 1/4" NPT-F.



gr. 440 oz. 15.4

280 bar-4050 PSI, 40 I/min-10.50 GPM, 150 °C-300 °F.

CDR.7410

CdR 70 extension lance without nozzle holder, 580 mm-23"

Made of chromed steel, inlet M 22x1,5 M,



outlet G 1/4" M.

gr. 400 oz. 14.0

280 bar-4050 PSI, 40 I/min-10.50 GPM, 150 °C-300 °F.

ZX.7140

CdR 7 nozzle holder with blue protection.

Made of stainless steel, inlet G 1/4" F, outlet 1/4" NPT-F.



gr. 45 oz. 1.6 CDR.7026

H.p. ball quick nozzle holder with black protection.

Made of brass, inlet G 1/4" F, outlet "quick".



gr. 70 oz. 2.5 250 bar-3600 PSI, 30 I/min-8,00 GPM, 90 °C-195 °F.

Lances

gr. 45

oz. 1.6

- Double lances and surface cleaners

AL.391317

ZX.7113 CdR 7 nozzle holder with black protection.

Double lance 1005 mm, straight. inlet G1/4M, outet 2x1/4 NPT-F,

melted handle, with nozzle holder and protection

gr. 1100

oz. 38.5

280 bar-4050 psi, 40 l/min-10.50 USGpm, 150 °C-300 °F. Made of chromed steel pipe

MV.0202004721

Double lance extension 700 mm-27.6" with insulated handle,

inlet M 22x1,5 M, outlet 2 x 1/4" NPT-F,



AL.017433800

gr. 1100 oz. 38.5

280 bar-4050 psi, 40 I/min-10.50 USGpm, 150 °C-300 °F. Made of chromed steel pipe

CDR.0358

Plastic surface cleaner.

inlet M 22x1,5 F, 210 bar-*3050 psi*, 15 l/min-*4.00 USGpm*, 60 °C-*140 °F*

Suitable for semi-professional use. Rubber surface cleaner with revolution nozzles device. Rubber cover. stainless steel and brass revolving arm device, 400 mm-15.8" exstension.

gr. 3600

Supplied without nozzles

ZX.0339

oz. 126.0

Spray guns - Professionals

Spray gun SK2, inlet G 3/8" F, outlet G 1/4" F,

250 bar-3650 psi, 25 I/min-6.60 USGpm. 60 °C-140 °F

gr. 340



Spray gun SK2, inlet M 22x1,5 M, outlet G 1/4" F, 250 bar-3650 psi, 25 I/min-6.60 USGpm. 60 °C-140 °F

gr. 340 oz. 11.9

gr. 11

oz. 0.4

CDR.0300 Spray gun,

compensated blue, inlet G 3/8" F, outlet G 1/4" F 350 bar-5100 psi, 30 I/min-8.00 USGpm 160 °C-320 °F

gr. 660 oz. 23.1

oz. 11.9

CDR.1259

AL.017433804

RL56 spare parts kit



VEGA spare parts kit



CDR.0955

MV 920 spare parts kit



gr. 16

oz. 0.6

Copyright @2008 Idrobase. All rights reserved.

gr. 11 oz. 0.4