

# HW SERIES Industrial Duty Plunger Pumps

1450 RPM

1750 RPM

3400 RPM

 Reversible Crankcase for Easy Right or Left Hand Mounting

Solid Brass Manifolds •

Solid or Hollow Shaft •

 Hardened Stainless Steel Piston Guides


Special Forged Brass • Oversized Connecting Rods

 Highly Efficient Stainless Steel Check Valves

Flange for Direct • Mounting to Gas Engines (Hollow Shaft Models Only.)

 Solid Ceramic Plungers

Die-Cast, Anodized • Aluminum Crankcase



High Quality Tapered Roller Bearings •

Optimal Oil Bath for High Speed Operation •

## $\mathsf{HW}$

## **Series Pumps-Solid Shaft**



### 1450 RPM - 24mm Solid Keyed Shaft

- 1/2" FPT Inlet, 3/8" FPT Discharge
- Anodized, Die-Cast Aluminum Crankcase
- Solid Ceramic Plungers
- Stainless Steel Check Valves
- Stainless Steel Piston Guides
- Buna-Textile V-Packings
- Oversized Bronze Connecting Rods
- Reversible Crankcase for Right or Left Hand Mounting
- 24mm Solid, Keyed Shaft

MODEL#	<u>GPM</u>	<u>PSI</u>	<u>RPM</u>	<u>SHAFT</u>	<u>PISTON</u>	<u>W I.</u>
HW 3540 S	3.4	4000	1450	24mm Solid	18mm	20.0
HW 4040 S	4.0	4000	1450	24mm Solid	18mm	20.0
HW 4540 S	4.4	4000	1450	24mm Solid	18mm	20.0

### **HW Series Mounting Rail Kits**

5011.0185.00 Standard Mounting Rail Kit for HW Series Pumps5011.0216.00 Tall Mounting Rail Kit for HW Series Pumps

#### **HW Series Repair Kits**

**5025.0011.00** Check Valve Kit **5019.0631.00** HW Seal Kit, 18mm

**2409.0073.00** HW Piston Kit, 18mm **5019.0044.00** HW Oil Seal Kit Solid Shaft