
20", HEAVY DUTY COMPOSITE



The following comparison chart shows the time taken to clean a typical size driveway (400 sq. ft.) using 3 different components.

Unit	Time to clean
	10 Minutes
Water Broom	30 Minutes
Spray Nozzle	80 Minutes

Whirl-A-Way Rotary Head Breakdown



Optional Kits Part# Ball Valve Kit 85.300.044 Allows you to switch between Whirl-A-Way and Wand without having to shutdown the unit.



very well at cleaning



Replacement Part Part# 85.790.004 **Rotary Head** 85.791.013 **Rotary Arm** 85.790.010 Rotary Head Repair Kit 85.225.025 Replacement Nozzle Tip 85.790.014 Nylon Bursh Skirt 85.202.115 Replacement Spray Gun

Nodel#	Max Pressure Max Flow		Max Temp.		Size	Weight
	4,000 PSI	8.0 GPM		160°F	20" diameter	32 lbs.
Feature			Pic	Feature		
Durable Nylon Brush Skirt	5 Welded Elbows and Assembly					
Heavy Duty Polypropylene Cover	6 Field Repairable Gun					
4,000 PSI Rotary Head, 160°F	Water Flow Out Front Prevents Cavitation				itation	
Welded Steel Rotary Arm			•	Zero Wall Clearance		
	Feature Durable Nylon Brush Skirt Heavy Duty Polypropylene Cover	4,000 PSI Feature Durable Nylon Brush Skirt Heavy Duty Polypropylene Cover 4,000 PSI Rotary Head, 160°F	4,000 PSI8.0 GPMFeatureDurable Nylon Brush SkirtHeavy Duty Polypropylene Cover4,000 PSI Rotary Head, 160°F	4,000 PSI8.0 GPMFeaturePicDurable Nylon Brush Skirt5Heavy Duty Polypropylene Cover64,000 PSI Rotary Head, 160°F•	4,000 PSI8.0 GPM160°FFeaturePicFeatureDurable Nylon Brush Skirt5Welded ElbowHeavy Duty Polypropylene Cover6Field Repairab4,000 PSI Rotary Head, 160°F•Water Flow Out	4,000 PSI 8.0 GPM 160°F 20" diameter Feature Pic Feature Durable Nylon Brush Skirt 5 Welded Elbows and Assembly Heavy Duty Polypropylene Cover 6 Field Repairable Gun 4,000 PSI Rotary Head, 160°F • Water Flow Out Front Prevents Cav

