

Soap For Hope

ENVIROSPEC DONATES
100% OF PROFITS

from chemical sales to the following

CHARITIES



This quality product is Manufactured by:

EnviroSpec

a Division of Hi-Tech Jetting Technologies, Inc.
751 MLK Hwy. • Homerville, GA 31634

For further information call:
1-800-346-4876

READ & UNDERSTAND

the Material Safety Data Sheet Prior to Use
If no MSDS is present call
1-800-346-4876

For Industrial or Professional Use Only
KEEP OUT OF REACH OF CHILDREN

LAUROX LO

HEALTH & SAFETY INFORMATION EFFECTS OF OVER EXPOSURE

- **Ingestion:** May produce gastrointestinal disturbances including irritation, nausea, & diarrhea.
- **Eyes:** Causes moderate to severe eye irritation and possible eye injury.
- **Skin:** Causes skin irritation
- **Inhalation:** May be irritating to the respiratory system.

Emergency First Aid Procedures:

- **Ingestion:** Do Not induce vomiting. Call physician and follow recommendations given. Never give anything by mouth to an unconscious person
- **Eyes:** Immediately flush eyes with flowing water for at least 15 minutes, holding eyelids apart to irrigate thoroughly. If irritation persist get medical attention.
- **Skin:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing. If irritation persist get medical attention.
- **Inhalation:** Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get immediate medical attention.

FOR PROFESSIONAL USE ONLY

FUNCTIONAL PROPERTIES

- **BLEACH STABLE**
- **ACID STABLE**
- **FOAM GENERATOR**
- **EMULSIFIER**
- **FOAM STABILIZER**
- **WETTING AGENT**
- **VISCOSITY BUILDER**

LAUROX LO is a unique blend of AMMONYX® LO, solvents, water softeners and quick rinse additives.

With the addition of LAUROX LO to bleach, detergent or acids you can expect a dramatically enhanced 'dwell time', exceptional cleaning characteristics and a quick rinse.

Add to product in levels
from 3% to 10% by weight

