

This quality product is Manufactured by:

EnviroSpec

a Division of Hi Tech Jetting Technologies, Inc.
751 MLK Hwy. • Homerville, GA 31634

For further information call: 1-800-346-4876

READ & UNDERSTAND

the Material Safety Data Sheet Prior to Use If no MSDS is present call 1-800-346-4876

For Industrial or Professional Use Only KEEP OUT OF REACH OF CHILDREN

PERFORMANCE BUILDER

is our additive for liquid caustics.

This product is meant to be mixed and used within a mixture.

Adds Excellent
CLEANING, WETTING, & RINSING PROPERTIES
to your Product

This Product is an ADDITIVE FOR CAUSTICS

BLENDING INSTRUCTIONS:

After mixing your caustic soda beads with 55 gallons of water, pour in Performance Builder to obtain excellent cleaning, wetting, and rinsing from your product.

This product consists of five gallons of surfactant, rinse agents, colorization, & builders.

Performance Builder contains all the additive ingredients you will need to add to a 50 pound bag of Caustic Soda Beads or to a 55 gallon drum of Potassium Hydroxide.

In case of spill call CHEMTREC 1-800-424-9300

Health & Safety Information EFFECTS OF OVER EXPOSURE

•Ingestion: Damage to renal system may occur

•Eyes: Causes severe eye irritation

•Skin: Causes skin irritation

•Inhalation: Causes respiratory tract irritation

Emergency First Aid Procedures:

•Ingestion: Contact physician or poison control center immediately. Get immediate medical help.

•Eyes: Immediately flush with copious amounts of water for at least 15 minutes or until all material is removed. If irritation develops or persists, get medical attention.

•Skin: Immediately remove contaminated clothing and flush area with large quantities of water and soap for at least 15 minutes. Launder clothes before reuse. If irritation develops or persists, get medical attention.

•Inhalation: Remove from contaminated atmosphere. Get immediate medical attention.