


Vehicle Cleaning Plunger Pumps


PDCW-Series Car Wash Pumps



- 24 mm Solid, Keyed Shaft or 5/8" Hollow Shaft
- Brass Manifold
- Stainless Steel Check Valves
- Stainless Steel Plunger Rods
- Solid Ceramic Plungers

	MODEL	GPM	PSI	POWER REQUIREMENTS	INLET	DISCHARGE	WEIGHT	LIST PRICE
1750 RPM	PDCW 4.0/15-S	4.0	1500	4.0 HP Electric	3/8" FNPT	3/8" FNPT	12 lbs.	\$346.00
	PDCW 4.0/15-Z	4.0	1500	4.0 HP Electric	3/8" FNPT	3/8" FNPT	13 lbs.	\$346.00


SUPER DUTY MKCW-Series Car Wash Pump



- Dual 20 mm Solid, Keyed Shaft
- Direct, Bolt-in Replacement for '310'
- Includes Rails, Thru-Shaft Protector
- Double Lip Oil Seals
- Brass Manifold
- Bronze Connecting Rods
- Stainless Steel Check Valves
- Custom, Stepped Plunger Rods

	MODEL	GPM	PSI	POWER REQUIREMENTS	INLET	DISCHARGE	WEIGHT	LIST PRICE
950 RPM	MKCW-3100	4.0	2000	5 HP Electric	1/2" FNPT	3/8" FNPT	32 lbs.	\$645.00


SUPER DUTY GKCW-Series Car Wash Pumps



- 24 mm Solid, Keyed Shaft
- Bronze Connecting Rods
- Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold
- Tapered Roller Bearings
- Stainless Steel Plunger Rods

	MODEL	GPM	PSI	POWER REQUIREMENTS	INLET	DISCHARGE	WEIGHT	LIST PRICE
1100 RPM	GKCW 18/14-S	5	2000	7.5 HP Electric	3/4" FNPT	3/8" FNPT	39 lbs.	\$700.00
	GKCW 21/14-S	6	2000	10.0 HP Electric	3/4" FNPT	3/8" FNPT	39 lbs.	\$700.00
	GKCW 30/14-S	8	2000	12.5 HP Electric	3/4" FNPT	3/8" FNPT	39 lbs.	\$750.00
	GKCW 38/14-S	10	2000	15.0 HP Electric	3/4" FNPT	1/2" FNPT	39 lbs.	\$770.00

GSCW-Series Car Wash Pumps



- 35 mm Solid, Keyed Shaft
- Bronze Connecting Rods
- Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifolds
- Tapered Roller Bearings
- Stainless Steel Plunger Rods

	MODEL	GPM	PSI	POWER REQUIREMENTS	INLET	DISCHARGE	WEIGHT	LIST PRICE
900 RPM	GSCW 50/NB	12	1500	12.5 HP Electric	1" FNPT	3/4" FNPT	80 lbs.	\$2,100.00
1200 RPM	GSCW 60/NB	16	1500	15.0 HP Electric	1" FNPT	3/4" FNPT	80 lbs.	\$2,140.00