

Cat 5CP3120



Comet HWS3540



General TS1511



STAINLESS STEEL

COOLDRIVE



Distinguishing Features

- 1 Patented Cooling Technology
- 2 Cool Air Ventilation Slots
- 3 Perm-A-Line Belt Tension System
- 4 Laser Aligned Pulley Fanning System
- 5 Quick-Release Belt Guard Knobs
- 6 Free Standing S.Steel Belt Guard
- 7 Flat-Free Foam Filled Tires
- 8 Industrial Aluminum Mags
- 9 Block Mounted Unloader




| Model# | Engine | Pump | PSI | GPM | Weight |
|--------|-----------------------------|----------------|-------|-----|---------|
| | Honda 13 HP GX390 Oil Alert | Cat 5CP3120 | 3,500 | 4.0 | 210 lbs |
| | Honda 13 HP GX390 Oil Alert | Comet HWS3540 | 4,000 | 3.5 | 210 lbs |
| | Honda 13 HP GX390 Oil Alert | General TS1511 | 3,500 | 4.0 | 210 lbs |

| Pic | Feature | Pic | Feature | Pic | Feature |
|-----|--------------------------------|-----|------------------------------------|-----|------------------------------------|
| | • 14,000 Cleaning Units | 2 | 13" Foam Filled Tires | 7 | 4 Quick-Connect Spray Tips |
| | • Honda 13 HP GX390 Gas Engine | 3 | Chemical Injector | | • Industrial Triplex Pump |
| 1 | 'EZ Start' Adjustable Unloader | 4 | 50' Steel Braided Non-Marking Hose | | • Stainless Steel Frame |
| | • Thermal Relief Valve (145°) | 5 | 5,000 PSI Spray Gun | | • Belt Drive |
| | • Safety Relief Valve | 6 | 36" Insulated Lance | | • Box Dimensions: H27", L33", W27" |



**HONDA
ENGINES**



33"