

HEALTH AND SAFETY INFORMATION

Effects of Over Exposure:

- **Ingestion:** Damage to renal system may occur.
- **Eyes:** Causes severe eye irritation.
- **Skin:** Causes skin irritation.
- **Inhalation:** Causes respiratory tract irritation.

Emergency First Aid Procedures:

- **Ingestion:** Drink large quantities of water or milk and allow vomiting to occur. Examine victim for possible corrosive injury to mouth and throat and irrigate the areas with 1% Acetic Acid until alkali is neutralized. Seek medical attention immediately.
- **Eyes:** Remove contact lenses. Flush with copious amounts of water until all material is removed. If irritation develops or persists, seek medical attention immediately.
- **Skin:** Wash contacted area with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.
- **Inhalation:** Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulties persist seek medical attention.

IN CASE OF EMERGENCY CALL

CHEMTREC
1-800-424-9300

READ & UNDERSTAND

the Material Safety Data Sheet prior to use.
If no MSDS is present call: 1-800-346-4876

For Industrial or Professional Use Only.
KEEP OUT OF REACH OF CHILDREN & ANIMALS

PERFORMANCE BUILDER

ADDITIVE FOR LIQUID CAUSTICS
HOOD CLEANER • HIGH FOAMING

BLENDING INSTRUCTIONS

Performance Builder contains all the additive ingredients you will need to add to a 50 pound bag of Caustic Soda Beads or to a 55 gallon drum of Potassium Hydroxide. Exercise caution when mixing sodium hydroxide beads with water. Add caustic soda beads very slowly otherwise there can be a violent explosive reaction where the product will blow back on you. For your maximum protection we strongly recommend that you wear protective clothing, gloves, full face shield, rubber boots and respirator when mixing sodium hydroxide with water.

After mixing your caustic soda beads with water and after it cools, slowly stir 1 gallon of Performance Builder into 55 gallons of water/product mix. This product will provide excellent cleaning, wetting, and rinsing qualities.

If you use Potassium Hydroxide you will purchase that in an 85% liquid form. Typically a manufacturer will make 4 drums out of 1 drum of the 85% solution. In this case you will need 4 each 1 gallon containers of Performance Builder Plus.

This Quality Product is Manufactured by:

ENVIROSPEC

A Division of Hi-Tech Jetting Technologies, Inc.