

## HEALTH AND SAFETY INFORMATION

### Effects of Over Exposure:

- **Ingestion:** Damage to renal system may occur.
- **Eyes:** Causes severe eye irritation.
- **Skin:** Causes skin irritation.
- **Inhalation:** Causes respiratory tract irritation.

### Emergency First Aid Procedures:

• **Ingestion:** Drink large quantities of water or milk and allow vomiting to occur. Examine victim for possible corrosive injury to mouth and throat and irrigate the areas with 1% Acetic Acid until alkali is neutralized. Seek medical attention immediately.

• **Eyes:** Remove contact lenses. Flush with copious amounts of water until all material is removed. If irritation develops or persists, seek medical attention immediately.

• **Skin:** Wash contacted area with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.

• **Inhalation:** Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing difficulties persist seek medical attention.

IN CASE OF EMERGENCY CALL

**CHEMTREC**  
**1-800-424-9300**

### READ & UNDERSTAND

the Material Safety Data Sheet prior to use.  
If no MSDS is present call: 1-800-346-4876

For Industrial or Professional Use Only.  
KEEP OUT OF REACH OF CHILDREN & ANIMALS

# PLEX-MASTER

## HOUSE WASH SURFACE SEALANT MILDEW FORMATION RETARDANT

### BLENDING INSTRUCTIONS

Pre-mix 5 gallons of Plex-Master with 55 gallons of water. Further dilute by means of an Allison Super Suds Sucker, down-stream injector - our part number 1964.

### USE INSTRUCTIONS

Work in small sections to avoid product from drying on the surface before rinsing. Rinse thoroughly. Plex-Master should not be applied to any surface if the homeowner is planning on painting during the next 12-15 months.\* Because of the unique hardeners used in the formulation, Plex-Master will remain on the surface for a long period of time. Mildew will be much easier to remove when there is a coating of Plex-Master on the substrate. In most cases, the homeowner will be able to keep the surface alive and free of mildew with a weekly rinse with the garden hose.

*\*It is recommended that you re-clean the surface using Prodigy before your customer paints. By doing so your customer can be assured that all of the Plex-Master has been removed and the paint will adhere to the surface.*

## MAKES GLASS SPARKLE!

This Quality Product is Manufactured by:

**ENVIROSPEC**

A Division of Hi-Tech Jetting Technologies, Inc.

