

RWS

Series Pumps-Solid Shaft

1750 RPM - 24mm Solid Shaft

- 1/2" FPT Inlet, 3/8" FPT Discharge
- Crankcase: Die-Cast Aluminum Alloy
- Solid Ceramic Plungers
- Forged Brass Manifold
- Oversized Bronze Connecting Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication
- Oil Cap: New Travel/Working Oil Cap



MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
RWS 6020 S	5.9	2000	1750	24mm	20mm	27.0
RWS 6520 S	6.6	2000	1750	24mm	20mm	27.0
RWS 3030 S	3.0	3000	1750	24mm	20mm	27.0
RWS 3530 S	3.6	3000	1750	24mm	20mm	27.0
RWS 4030 S	4.1	3000	1750	24mm	20mm	27.0
RWS 4530 S	4.4	3000	1750	24mm	20mm	27.0
RWS 5030 S	4.9	3000	1750	24mm	20mm	27.0
RWS 5530 S	5.7	3000	1750	24mm	20mm	27.0
RWS 3035 S	3.0	3500	1750	24mm	20mm	27.0
RWS 5535 S	5.7	3500	1750	24mm	20mm	27.0
RWS 3540 S	3.6	4000	1750	24mm	18mm	27.0
RWS 4040 S	4.0	4000	1750	24mm	18mm	27.0
RWS 4540 S	4.8	4000	1750	24mm	18mm	27.0
RWS 5040 S	5.3	4000	1750	24mm	18mm	27.0
RWS 6040 S	6.0	4000	1750	24mm	18mm	27.0

RWS

Series Pumps-Electric

1750 RPM - 1-1/8" Hollow Shaft

- 1/2" FPT Inlet, 3/8" FPT Discharge
- Crankcase: Die-Cast Aluminum Alloy
- Solid Ceramic Plungers
- Forged Brass Manifold
- Oversized Bronze Connecting Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication
- Oil Cap: New Travel/Working Oil Cap
- 184T Electric Flange with 1-1/8" Hollow Shaft



MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.
RWS 3530 E	3.6	3000	1750	1 1/8" Hollow	20mm	27.0
RWS 4030 E	4.1	3000	1750	1 1/8" Hollow	20mm	27.0
RWS 4530 E	4.4	3000	1750	1 1/8" Hollow	20mm	27.0
RWS 5030 E	4.9	3000	1750	1 1/8" Hollow	20mm	27.0
RWS 5530 E	5.7	3000	1750	1 1/8" Hollow	20mm	27.0