

SW SERIES

Premium Pumps



1450 RPM 1750 RPM24mm Solid K eyed Shaft

- Heavy Duty up to 4000 PSI
- High Volume up to 5.5 GPM
- Long Life Seals
- One Piece, Solid Bronze Alloy Connection Rods
- Solid Shaft 24mm for Belt Drive, Gearbox or Flex Couplers
- Oil Cap: New Travel/Working Oil Cap
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life
- 1/2" FPT Inlet, 3/8" FPT Discharge
- Crankcase: Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 4000 PSI

SW

Series Pumps-Solid Shaft

MODEL #	<u>GPM</u>	<u>PSI</u>	<u>RPM</u>	SHAFT	PISTON	<u>WT.</u>
SW 4040 S	4.0	4000	1450	24mm	20mm	39.0
SW 4040 S*	4.0	4000	1450	24mm	20mm	39.0
SW 5540 S	5.5	4000	1450	24mm	20mm	39.0
SW 5540 S*	5.5	4000	1450	24mm	20mm	39.0

^{*}Hot Water Pump with Kevlar Seals

SWS

Series Pumps-Solid Shaft

MODEL#	<u>GPM</u>	<u>PSI</u>	<u>RPM</u>	SHAFT	PISTON	WT.
SWS 5025 S	5.0	2500	1750	24mm	20mm	39.0
SWS 4040 S	4.0	4000	1750	24mm	20mm	39.0
SWS 4040 S	* 4.0	4000	1750	24mm	20mm	39.0

^{*}Hot Water Pump with Kevlar Seals

SW Series Mounting Rail Kits

5011.0214.00 Standard Mounting Rail Kit for SW/TW Series Pump

SW Series Repair Kits

5025.0011.00 Valve Kit 2409.0074.00 Piston Kit, 20mm 5019.0648.00 Seal Kit, Water 5019.0650.00 Oil Seal Kit 5019.0665.00 SW Seal Kevlar Kit 20mm 5019.0670.00 SW Hot Water Seal Kit, 20mm