

SIL-O-WET



ENVIROSPEC
1-800-346-4876

Sil-O-Wet

is a blend of silicone, polymers and hardeners similar to Plex-Master, but with extra hardeners that allow it to last up to three years.

Formulated for the Exterior House Wash Industry

**This Product Contains:
“High Yield Gloss Enhancers”**

This Quality Product is Manufactured by:

ENVIROSPEC

a Division of: Hi Tech Jetting Technologies, Inc.
751 MLK Hwy. • Homerville, GA 31634

For further information call:
1-800-346-4876

DISTRIBUTED BY:

SURFACE SEALANT WITH MILDEW FORMATION RETARDANT

BLENDING INSTRUCTIONS

Sil-O-Wet can be used to seal house siding, bricks, and concrete as well as asphalt roofs.

For further dilution through a down stream injector, pre-dilute 1 part product to whichever part water as shown below:

House siding & Bricks.....9 parts water
Concrete Floors.....4 parts water
Asphalt Roofs.....4 parts water
Tile Roofs.....7 parts water

For direct spray applications dilute 1 part product to whichever part water as shown below:

House Siding.....50 parts water
Bricks.....50 parts water
Concrete Floors.....25 parts water
Asphalt Roofs.....25 parts water
Tile Roofs.....40 parts water

USE INSTRUCTIONS:

Work in small sections to avoid product from drying on the surface before rinsing. Rinse thoroughly.

Sil-O-Wet should not be applied to any surface if the homeowner is planning on painting during the next 24-36 months. Because of the unique hardeners used in the formulation, **Sil-O-Wet** will remain on the surface for a long period of time.

Applying **Sil-O-Wet** to the surface after restoring old brick will generally turn the the brick 3-4 shades darker producing a much richer look.

Emergency First Aid Procedures:

• **Ingestion:** If swallowed, do NOT induce vomiting. Give large quantities of water or milk. Never give anything by mouth to an unconscious person. Get immediate medical attention.

• **Eyes:** Irritating, and may injure eye tissue if not removed promptly. Immediately flush eyes with large amounts of water for at least 15 minutes. Get prompt medical attention.

• **Skin:** Low order of toxicity. Irritating. Flush with large amounts of water. Launder contaminated clothing before reusing. If irritation persists, seek medical attention.

• **Inhalation:** Remove to fresh air. Get immediate medical attention.

READ & UNDERSTAND

the MSDS Prior to Use

If none is present call

1-800-346-4876

For Industrial or Professional Use Only

**KEEP OUT OF REACH
OF CHILDREN**