# **Hose Reels**

## Aluminum and Stainless



#### Manual rewind with U-channel frame

Series	Frame	Inlet / Outlet	Manifold	Max feet of hose (dia.)
4800	Aluminum	1/2" npt	Black iron	325 (1/2")
5400	Stainless	1/2" npt	Stainless	325 (1/2")



## Manual rewind with full frame and pinlock

Series	Frame	Inlet / Outlet	Manifold	Max feet of hose (dia.)
4300	Aluminum	1/2" npt	Black iron	500 (1/2")
5500	Stainless	1/2" npt	Stainless	500 (1/2")
4000	Aluminum	1" npt	Black iron	90 (1")



## 12 volt electric rewind with optional hose guide

Series	Frame	Inlet / Outlet	Manifold	Max feet of hose (dia.)
Selles	i iaiii <del>c</del>	Outlet	Marillolu	1105e (dia.)
4300E 5500E 4000E	Aluminum Stainless Aluminum	1/2" npt 1/2" npt 1" npt	Black iron Stainless Black iron	500 (1/2") 500 (1/2") 90 (1")

See price list for individual model specs.

All handles, tierods, and hardware are stainless steel. Spools are heavy duty PVC. Swivels are available in stainless steel, and nickel plated steel with grease fitting. Pressure rating is 3000 or 5000 psi. Electric rewind reels include prewired switch and solenoid.