



TW SERIES

Premium Pumps



24mm Solid Keyed Shaft

- Heavy Duty up to 5000 PSI
- High Volume up to 13.0 GPM
- Long Life Seals

- 1/2" or 3/4" FPT Inlet, 3/8" FPT Discharge
- Crankcase: Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 5000 PSI
- One Piece, Solid Bronze Alloy Connection Rods
- Solid Shaft 24mm for Belt Drive, Gearbox or Flex Couplers
- Oil Cap: New Travel/Working Oil Cap
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life

TWN

Series Pumps-Solid Shaft

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.	INLET
TWN 7025 S	7.0	2500	1000	24mm	25mm	45.0	3/4"
TWN 8025 S	8.0	2500	1000	24mm	25mm	45.0	3/4"
TWN 6036 S	6.0	3600	1000	24mm	22mm	45.0	1/2"

TW

Series Pumps-Solid Shaft

MODEL #	GPM	PSI	RPM	SHAFT	PISTON	WT.	INLET
TW 11025 S	11.0	2500	1450	24mm	25mm	45.0	3/4"
TW 11025 S*	11.0	2500	1450	24mm	25mm	45.0	3/4"
TW 10025 S	10.0	2500	1450	24mm	25mm	45.0	3/4"
TW 8030 S	8.7	3000	1450	24mm	22mm	45.0	3/4"
TW 8030 S*	8.7	3000	1450	24mm	22mm	45.0	3/4"
TW 7036 S	7.0	3600	1450	24mm	22mm	45.0	3/4"
TW 8036 S	8.6	3600	1450	24mm	22mm	45.0	3/4"
TW 4550 S	4.7	5000	1450	24mm	18mm	45.0	1/2"
TW 5050 S	5.2	5000	1450	24mm	18mm	45.0	1/2"
TW 5550 S	5.8	5000	1450	24mm	18mm	45.0	1/2"

*Hot Water Pump with Kevlar Seals