

# Rapid Rise Model

Sidewalls Stay Lowered And Out Of The Way Until They Are Needed



- Sidewalls remain down during normal operations, loading and unloading. Vehicles and equipment can drive in and out from any angle, with no sidewall set-up or take-down required.
- In the case of a spill, the foam ring around the top perimeter of the Containment Berm rises with the level of spilled liquid.
- Custom sizes available.
- Standard material of construction is Copolymer 2000™.
- Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175.



## ULTRA-CONTAINMENT BERMS, RAPID RISE MODEL

Part #	Dimensions	Weight	Containment Capacity
	4' x 6' x 1' (1.2 m x 1.8 m x .3 m)	29 lbs. (13 kg)	179 gallons (678 L)
	6' x 6' x 1' (1.8 m x 1.8 m x .3 m)	35 lbs. (16 kg)	269 gallons (1,018 L)
	10' x 10' x 1' (3 m x 3 m x .3 m)	63 lbs. (29 kg)	748 gallons (2,831 L)
	12' x 26' x 1' (3.7 m x 7.9 m x .3 m)	149 lbs. (67.5 kg)	2,333 gallons (8,831 L)
	15' x 50' x 1' (4.6 m x 15.2 m x .3 m)	278 lbs. (126.5 kg)	5,610 gallons (21,234 L)
	15' x 66' x 1' (4.6 m x 20.1 m x .3 m)	357 lbs. (162 kg)	7,405 gallons (28,028 L)

Material of Construction: Copolymer 2000™ an ethylene copolymer, is standard. Copolymer 3000™, XR5, polyurethane and other materials are also available on a custom basis.  
Options: Ground Tarps, Track Belts, Self Bailer, see page 31.