MATERIAL	SAFE	ΓΥ D	ATA	SH	EE	Т			
OSHA - Meets 29 CFR 1910.1200 Standards	HMIS HAZARD RATINGS								
Soap For Hope	HEALTH FLAMMABILITY PHYSICAL HAZ		2 (* = Chronic 0 = INSIGN 1 = SLIGH ⁻	IFICANT		2 = MODE 3 = HIGH 4 = EXTRE		
Touching a Life one Bubble at a Time		TRA	NSPORTAT	ION INFO	ORMATI	ON			
Over 60% of the profits derived from the manufacturing of EnviroSpec Cleaning Chemicals are donated nationally to Charities for Children & Animals	PROPER SHIP HAZARD CLAS IDENTIFICATIO	S / PKG GRP	Not Regula : Not regulat None	ed	REF: LABEL:	Not Applic None Req			
SECTION 1 - PRODUCT / COMPAN	Y IDENTIFI	CATION							
IDENTITY (AS USED ON LABEL AND LIST) VIPER-Y-O						F	Page 1 of 2		
MANUFACTURER'S NAME EnviroSpec		EMERGENCY TELEPHONE NUMBER Chemtrec (800) 424-9300 Outside USA (703) 527-3887							
ADDRESS (NUMBER, STREET, P.O. BOX) 751 MLK Highway		TELEPHONE NUMBER FOR INFORMATION (912) 487-1778							
(CITY, STATE AND ZIP CODE) Homerville, GA 31634		DÀTE PREPARED: JULY 11, 2011 SUPERSEDES: New							
SECTION 2 - HAZARDOUS INGRE	DIENTS / ID			-	1				
HAZARDOUS COMPONENTS		<u> </u>				H TWA	SARA	RQ	
(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	(OPTIONAL)		MG/M3	PPM	MG/M3	TITLE III	LBS	
Sodium phosphate, tribasic (STPP) (a)	7758-29-4	60 - 90	not est	ablished				5000	
Ethylene glycol monobutyl ether (b,c)	111-76-2	10 - 30		240	20)	Yes		
(a) The Comprehensive Environmental Response, Compensa					ents for re	eleases or s	spills to the		
environment of the Reportable Quantity (RQ for this mixture = 7,000 lbs) or greater amounts, according to 40 CFR 302. (b) A "Yes" in the SARA TITLE III column in Section 2 indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.									
(c) Indicates an employee's skin exposure shall be prevented goggles, or other appropriate equipment.	or reduced to the	extent necessa	ary in the circu	imstances i	through th	ne use of glo	oves, covera	alls,	
						····			
SECTION 3-HEALTH HAZARD DA	1 <i>7A</i>					· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		
ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE			Y AND FIRST A						
INHALATION: Breathing dusts may cause irritation of respiratory tract.		Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.							
SKIN: Prolonged contact may cause irritation.		Wash contacted area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention.							
		with chemic	ar agents, ir in		51515, 5661				
EYES: Contact with eyes will cause irritation.		Check for and remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention							
		immediately	-	lo nolaling (oyondo op				
INGESTION: May cause gastric distress, vomiting and diarrh	ea.		quantities of w mouth to an u /.						
CARCINOGENICITY	NTP?	No	IARC MON	OGRAPHS?	No	OSHA F	REGULATED?	No	
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EX prolonged exposure.	XPOSURE: Preex	isting skin, eye	e, or respirator	y disorders	s may bec	ome aggrav	vated throug	Jh	

MATERIAL SAFETY DATA SHEET								
IDENTITY (AS USED ON LABEL AND LIST)			Page 2 of 2					
VIPER			Date: JULY 11, 2011					
SECTION 4 - FIRE FIGHTING MEAS	SURES							
FLASH POINT (METHOD USED)	NFPA RATIN	IG FLAMMABLE LII	MITS					
165° F (73.9° C)	NEEADATIN	LEL: 1.1%	UEL: 10.6%					
EXTINGUISHING MEDIA	None		022. 10.070					
Carbon dioxide, water, water fog, dry chemical, chemical foar	m.							
SPECIAL FIRE FIGHTING PROCEDURES								
Airborne dusts may form explosive mixtures if allowed to con-	centrate in confined ar	ea. Contact with strong oxidizers	s may cause fire.					
UNUSUAL FIRE AND EXPLOSION HAZARDS Heated powders will emit combustible vapor of the glycol ether.								
SECTION & ACCIDENTAL DELEAS		c						
SECTION 5-ACCIDENTAL RELEASE MEASURES								
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OF eyes. Wash small spills to sanitary sewer. Large spills - confir								
limits (RQ) notify the National Response Center (800) 424 - 880								
CFR 372 concerning reporting requirements.								
SECTION 6 - HANDLING AND STORAGE								
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE		ed when not in use: protect cont	ainers from abuse: protect from extreme					
temperatures. Store in cool, dry area. Keep this and other che			allers from abuse, protect from extreme					
SECTION 7 - EXPOSURE CONTROL	S / PERSON	I PROTECTION						
RESPIRATORY PROTECTION (SPECIFY TYPE): None requi			wable concentrations: if TWA exceeds					
limits, NIOSH approved respirator must be worn. Refer to 29 C								
VENTILATION LOCAL EXHAUST:	Required	SPECIAL: To maintain minimun	n TWA and STEL levels.					
MECHANICAL (GENERAL):	Yes	OTHER: Engineering and wor	k controls as required.					
PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs. EYE PROTECTION: Chemical safety goggles.								
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveral								
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.								
SECTION 8 - PHYSICAL / CHEMICAL	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·						
BOILING POINT		ECIFIC GRAVITY (WATER	= 1)					
Not applicable		2.5 - 2.8						
VAPOR PRESSURE (MM Hg) Not applicable		pH						
VAPOR DENSITY (AIR = 1)		11.5 - 12.5 (2% aqueous solution) EVAPORATION RATE (WATER = 1)						
Not applicable		Not applicable						
SOLUBILITY IN WATER		% VOLATILE (BY WEIGHT)						
Complete		< 17%						
APPEARANCE AND ODOR								
Yellow free flowing powder, characteristic orange odor								
SECTION 9-STABILITY AND REAC	CTIVITY							
STABILITY UNSTABLE:	CC	NDITIONS TO AVOID: Avoid g	enerating airborne dust.					
STABLE: 2								
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizer	s, strong acids, strong	alkalies.						
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decom	position will not occur	f bandlad and atorad properly. Ir	a case of a fire, avides of carbon					
hydrocarbons, fumes or vapors, and smoke may be produced.	position will not occur i	r nandied and stored propeny. Ir	T case of a life, oxides of carbon,					
HAZARDOUS POLYMERIZATION MAY OCCUR:	CC	NDITIONS TO AVOID: None						
WILL NOT OCCUR: 2								
SECTION 10 - DISPOSAL CONSIDE								
	· · · · · · · · · · · · · · · · · · ·	al Regulations Refer to "40 CF	R Protection of Environment Parts 260 -					
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for alkaline materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of								
any chemicals.								
The information contained herein is believed to be accurate bu	t is not warranted to	be so. Data and calculations a	re based on information furnished by the					
manufacturer of the product and manufacturers of the component	ts of the product. Use	rs are advised to confirm in ad	vance of need that information is current,					
applicable and suited to the circumstances of use. Vendor assur reasonable safety procedures are not adhered to as stipulated in t								
of this material even if reasonable safety procedures are followed								