



WT3000H



WC5000H



WC6000H/
WC6000HE

MODEL NUMBER	WT3000H	WC5000H	WC6000H	WC6000HE
Electrical Specifications				
Maximum Power Rating	3000 watts	5000 watts	6000 watts	6000 watts
Continuous Power Rating	2500 watts	4500 watts	5500 watts	5500 watts
A.C. Output Voltage	120 volts	120/240 volts	120/240 volts	120/240 volts
Continuous Current Rating	20.8 amps	37.5/18.8 amps	45.8/22.9 amps	45.8/22.9 amps
Motor Starting Ability (1)	1.0 hp	1.5 hp	3.0 hp	3.0 hp
120 Volt Full Power™ (3)	N/A	37.5 amps	45.8 amps	45.8 amps
Generator Type (4)	R.F.L.	R.F.L.	R.F.B.	R.F.B.
Engine Data				
Make/Model	Honda GX160	Honda GX270	Honda GX340	Honda GX340
Displacement/Type	160 cc/OHV	270 cc/OHV	337 cc/OHV	337 cc/OHV
Conserv-R® Automatic Idle Control	N/A	Standard	Standard	Standard
Low Oil Protection	Standard	Standard	Standard	Standard
Starting System (5)	Recoil	Recoil	Recoil	Recoil/Electric
Fuel Tank Capacity	1.0 Gallon	4.5 Gallons	4.5 Gallons	4.5 Gallons
Running Time-Full Load	2.2 hours	6.6 hours	5.2 hours	5.2 hours
Running Time-Half Load	3.1 hours	10.3 hours	9.8 hours	9.8 hours
Hour Meter	N/A	Standard	Standard	Standard
120 Volt Receptacles				
Straight Blade (NEMA 5-20R)	4-20 amp	4-20 amp GFCI	4-20 amp GFCI	4-20 amp GFCI
Twist Lock (NEMA L5-20R) GFCI Protected		2-20 amp	2-20 amp	2-20 amp
Straight Blade (NEMA 5-30R)				
Straight Blade (NEMA 5-50R)		1-50 amp	1-50 amp	1-50 amp
240 Volt Receptacles				
Twist Lock (NEMA L6-20R)		1-20 amp	1-20 amp	1-20 amp
Twist Lock (NEMA L6-30R)				
Straight Blade (NEMA 6-50R)				
120/240 Volt Receptacles				
Twist-Lock (NEMA L14-30R)	N/A	1-30 amp	1-30 amp	1-30 amp
Straight Blade (NEMA 14-60R)				
Size & Weight				
Dimensions (LxWxH)	24x16x18 in.	32x22x22 in.	32x22x22 in.	32x22x22 in.
Shipping Weight	102 lbs.	226 lbs.	251 lbs.	262 lbs.
Warranty Information (8)				
Generator/Engine	2 yrs/3 yrs	2 yrs/3 yrs	2 yrs/3 yrs	2 yrs/3 yrs
CSA Approved	Yes	Yes	Yes	Yes

* ENGINES: Premium Honda and Briggs & Stratton Vanguard CARB and EPA certified engines equipped with low oil protection and industrial grade mufflers * FRAMES: Heavy duty tubular steel cradles protect the generator; rubber isolation mounts on engine and generator, compact size for easy transportation and handling * FUEL TANKS: Large 4.5, 7.0 and 15.0 gallon fuel tanks for longer run times on 4kW and larger * CONTROL PANELS: Easy-access; wide variety of receptacles; circuit breaker protection * SUPERIOR GENERATOR END: 100% copper windings; high motor starting capabilities; self-regulating output voltage; built to last * FEATURES/STANDARDS: All units are 100% load tested; USFS-approved spark arrestors; WC models have Conserv-R® automatic idle control and hour meter.



MODEL NUMBER	W9500HE	WC12000HE	WL18000VE	Diesel W6010DEX
Electrical Specifications				
Maximum Power Rating	9500 watts	12000 watts	18000 watts	6000 watts
Continuous Power Rating	8500 watts	10800 watts	15000 watts	5500 watts
A.C. Output Voltage	120/240 volts	120/240 volts	120/240 volts	120/240 volts
Continuous Current Rating	70.8/35.4 amps	90/45 amps	125/62.5 amps	45.8/22.9 amps
Motor Starting Ability (1)	5 hp (7)	6 hp	7.5 hp	3.0 hp
120 Volt Full Power™ (3)	45.8 amps	N/A	N/A	45.8 amps
Generator Type (4)	R.F.L.	R.F.L.	R.F.L.	R.F.L.
Engine Data				
Make/Model	Honda GX610	Honda GX620	B&S Vanguard	Hatz 1B40
Displacement/Type	610 cc/OHV	620 cc/OHV	895 cc/OHV	462 cc
Conserv-R® Automatic Idle Control	N/A	Standard	N/A	N/A
Low Oil Protection	Standard	Standard	Standard	Standard
Starting System (5)	Electric	Electric	Electric	Electric
Fuel Tank Capacity	4.5 Gallon	15 Gallons	15 Gallons	7.0 Gallons
Running Time-Full Load	3.2 hours	9.0 hours	6.8 hours	10.0 hours
Running Time-Half Load	5.3 hours	14.5 hours	10.5 hours	20.0 hours
Hour Meter	N/A	Standard	Standard	Standard
120 Volt Receptacles				
Straight Blade (NEMA 5-20R)	4-20 amp GFCI	4-20 amp GFCI	4-20 amp GFCI	2-20 amp GFCI
Twist Lock (NEMA L5-20R) GFCI Protected	2-20 amp	1-20 amp	2-20 amp	
Straight Blade (NEMA 5-30R)				
Straight Blade (NEMA 5-50R)	1-50 amp		1-50 amp	1-50 amp
240 Volt Receptacles				
Twist Lock (NEMA L6-20R)	1-20 amp			
Twist Lock (NEMA L6-30R)		1-30 amp	1-30 amp	1-30 amp
Straight Blade (NEMA 6-50R)	1-50 amp			
120/240 Volt Receptacles				
Twist-Lock (NEMA L14-30R)	1-30 amp			1-30 amp
Straight Blade (NEMA 14-60R)		1-60 amp	1-60 amp	
Size & Weight				
Dimensions (LxWxH)	32x22x22 in.	39.5x26.5x26 in.	42x27x29 in.	32x22x22 in.
Shipping Weight	306 lbs.	440 lbs.	550 lbs.	300 lbs.
Warranty Information (8)				
Generator/Engine	2 yrs/3 yrs	2 yrs/3 yrs	2 yrs/2 yrs	2 yrs/2 yrs or 2000 hrs
CSA Approved	No	No	No	No