



# DL6000I & DL6000IE

## PORTABLE GENERATORS

### FOR HOME AND LIGHT INDUSTRIAL USE



- ▣ Compact, convenient, low-profile design
- ▣ Powerful Briggs & Stratton industrial OHV engine
- ▣ Electric or recoil start models
- ▣ Heavy duty generator with clean sine wave
- ▣ Large 4-1/2 gallon fuel tank
- ▣ CSA (Canadian Standards Association) approved

Building on nearly 80 years of experience, WINCO proudly introduces the new DL6000I and DL6000IE. Powered by the industrial Briggs & Stratton 11HP OHV Intek engine, these units are built with industrial components at a consumer-friendly price. A newly designed receptacle package features four 20-amp 120-volt receptacles and a full power 30-amp receptacle, all with circuit breaker protection. The heavy duty brushless alternator design minimizes maintenance by eliminating carbon brushes and slip rings common on competitive models, while simultaneously delivering voltage stability and clean power. The new Advance Power Series by DYNA is the perfect solution for reliable, industrial strength power for home back-up.

<u>TYPICAL POWER LOADS</u>	<u>POWER REQUIRED*</u>
Lights	As listed on light bulbs
TV, VCR/DVD Player, Stereo	150-300 watts
Computer, Monitor, Printer	800-1200 watts
Microwave Oven	600-1500 watts
Dishwasher	900-1200 watts
Toaster, Electric Fry Pan	1200 watts
Hair Dryer	800-1200 watts
Space Heater	1200-1500 watts
Portable Fan	200-300 watts
Furnace Fan	500-800 watts
Sump Pump	500-1200 watts
Refrigerator, Freezer	800-1500 watts
Drill (hand-held)	600-900 watts
Electric Hand Saw	1200-1500 watts
Portable Air Compressor	1200-1500 watts
Air Conditioner (window-mount)	1200-1500 watts
Air Conditioner (central air)	4000-6000 watts

\* Approximate power required for each item

# DYNA

## ADVANCE POWER

### DL6000I & DL6000IE PORTABLE GENERATORS



#### PERFORMANCE & TECHNICAL DATA\*\*

<b>Electrical Specifications</b>	<b>DL6000I</b>	<b>DL6000IE</b>
Maximum Power Rating (1)	6000 watts	6000 watts
Continuous Power Rating (1)	5500 watts	5500 watts
A C Output Voltage	120/240 volts	120/240 volts
Continuous Current Rating	45.8/22.9 amps	45.8/22.9 amps
Motor Starting Ability (2)	1.5 hp	1.5 hp
<b>Engine Data</b>		
Make/Model	B&S/Intek	B&S/Intek
Displacement/Type	342 cc/OHV	342 cc/OHV
Rated Power (3600 rpm)	11 hp	11 hp
Starting System	Recoil	Recoil/Elec
Fuel Tank Capacity	4.5 gallon	4.5 gallon
Low Oil Protection	Standard	Standard
Running Time - Full Load	5.3 hours	5.3 hours
Running Time - Half Load	8.5 hours	8.5 hours
<b>Receptacles</b>		
120V Straight Blade (NEMA 5-20R)	4-20 amp	4-20 amp
120/240V Twistlock (NEMA L14-30R)	1-30 amp	1-30 amp
<b>Size &amp; Weight</b>		
Dimensions (LxWxH)	26.25x17.5x21.4"	26.25x17.5x21.4"
Shipping Weight	158 lbs.	168 lbs.
<b>Warranty Information-Consumer Application (3)</b>		
Generator/Engine	2 yrs/2 yrs	2 yrs/2 yrs