



865 West 2600 South, Salt Lake City, UT 84119  
 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

**HYDROBLASTERS - HYDROKLEEN - HYDROPAD**

www.hydroblaster.com

## Hydroblaster™ CLOV Series

PART #	2/1000CLOV	3/1000CLOV	3/1500CLOV	4/2000CLOV	4/3000CLOV
VOLUME (GPM)	2.2	3	3	3.6	3.7
PRESSURE (PSI)	1000	1000	1500	2000	3000
ELECTRIC MOTOR (HP)	1.5	2.0	3	5	7.5
VOLTAGE <sup>1</sup> (STD)	(A)	(A)	(B)	(B)	(B) C, D
AMPERAGE	17	19	14	25	36,28, 14
BTU(PER HR. X 1000)	240	270	280	325	360
STACK SIZE (DIA)	8"	8"	8"	8"	8"
WEIGHT (LBS)	490	490	490	744	860
DIMENSIONS	25.75" wide X 45" long X 54" high				

<sup>1</sup> Voltage codes: A=120 Volt single phase, B=230 volt single phase, C=230 volt three phase, D=460 volt three phase.

### Standard Features:

- UL1776, CSA & CE Certified
- 8 gallon fuel tank with fuel gauge
- Heavy duty electric motor with reset on all 1 phase
- Schedule 80 steel coil
- Belt drive
- Full equipment covers
- Trigger gun
- Insulated variable pressure wand
- 15 degree nozzle
- 50' hose rated 3000 PSI
- Downstream chemical injection



Part#	Description	Availability and Dependencies
<b>Temperature Controls</b>		
*1SP592	High Limit Temperature Switch, 225°F	
2BY021	Thermostat, Adj.85-250°F, Rotary Switch	Required for steam combo option
1UF021	Thermostat, Adjustable	
<b>Steam Discharge Options</b>		
*2AR694	No Steam Combo	
1ZM383	Steam Combo, With Soap	
2BY020	Steam Combo	
<b>Electrical: Power &amp; Controls</b>		
*1ZR439	1.5HP,115 Volt, 1Phase, Rotary Switch	Standard on 2/1000
2AZ776	1.5HP,115 Volt, 1Phase, Rotary Switch, UL1776Portable	Available on 2/1000
1ZN392	208-230 Volt,1 Phase, Rotary Switch	Available on 3/1000, 2/1500, 4/2000, 4/3000
2BA780	208-230 Volt,1 Phase, Rotary Switch, UL1776 Portable	Available on 3/1000, 2/1500, 4/2000, 4/3000
1ZN393	208-230 Volt, 1 Phase, Contactor & Overload	Available on 3/1000, 2/1500, 4/2000, 4/3000
2BA782	208-230 Volt,1 Phase, Cont/Overload, UL1776 Portable	Available on 3/1000, 2/1500, 4/2000, 4/3000
1ZN394	208-230 Volt,3 Phase, Contactor & Overload	Available on 3/1000, 2/1500, 4/2000, 4/3000
1ZN395	460 Volt,3 Phase, Contactor & Overload	Available on 3/1000, 2/1500, 4/2000, 4/3000
1XT933	Shut Down Timer	Requires Contactor & Overload
<b>Remote Options</b>		
1UF028	Trigger Actuated Start	Requires Contactor & Overload and Shut Down Timer
1UF029	Remote On Off	
1UF030	Remote On Off, Burner On Off	
1VY462	Remote On/Off, Burner, Soap On Off	
<b>Hour Meter Option</b>		
*1SU640	No Hour Meter	
1WO621	Hour Meter For Rotary Switch	
1UF032	Hour Meter	
<b>Frame Options</b>		
*2CJ135	Painted Trim	
2CJ136	Stainless Trim	
<b>Stationary Or Portable Mount Options</b>		
*1XQ903	Stationary Kit, Legs	
1XQ902	Portability Kit, Casters	
<b>Discharge Options</b>		
*1YK108	Single High Pressure Nozzle, 15 degree	
1YK109	Four Nozzle Kit, 0,15,25,40 Degree	
1YL110	Turbo Nozzle	
1UF034	Hose Reel Kit, Wall Mount	
1WS663	Hose Reel Kit, Machine Mount.	
<b>System Gauge Options</b>		
*1UF035	No Pressure Gauge	
1UF036	Pressure Gauge	
1UF037	Temperature Gauge	
<b>Soap Options</b>		
*2AR698	Discharge Soap Injection	
1ZM389	Inlet Soap Injection	Requires Breaker Tank option
2GR259	Inlet Soap Solenoid Control	
<b>Breaker Tank Options</b>		
*2AR693	No Breaker Tank	
2AK620	Breaker Tank, Plastic	
2AK621	Breaker Tank, Stainless	

NOTE: \* reflects the standard



Quality Assured Firm  
 ISO 9001 Certified

