



865 West 2600 South, Salt Lake City, UT 84119
 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com

Hydroblaster™ EI Series
NSN: 4940-01-567-7391

| MODEL | 2/1000 | 3/1000 | 3/1500 | 2/2000 | 3/3000 |
|---------------------|--|--------------|------------------|--------------|--------------|
| VOLUME (GPM) | 2.2 | 3 | 3 | 2 | 2.5 |
| PRESSURE (PSI) | 1000 | 1000 | 1500 | 2000 | 3000 |
| ELECTRIC MOTOR (HP) | 1.5 | 2 | 3 | 3 | 5 |
| VOLTAGE | 120, 1 phase | 120, 1 phase | 230, 1 phase | 230, 1 phase | 230, 1 phase |
| AMPERAGE | 14 | 17 | 14 | 14 | 25 |
| ELECTRIC CORD | 6' GFCI cord | | No cord provided | | |
| WEIGHT | 70 | 78 | 85 | 85 | 135 |
| ELECTRICAL CONTROL | On/Off switch and motor overload protection. | | | | |
| OVERLOAD | Thermal sensing, manual reset. | | | | |
| DRIVE | Pump and motor are direct coupled. | | | | |
| LENGTH | | | | 20 | 23 |
| WIDTH | | | | 12 | 14 |
| HEIGHT | | | | 14 | 19 |

Standard Features:

- Direct drive, General Pump
- Heavy duty electric motor with reset
- Compact base with carry handle & adjustable feet
- 15' hose rated 3000 PSI
- Trigger gun with 36" wand
- Variable pressure/spray pattern nozzle
- 6' GFCI power cord on 110 volt models



| Part# | Description |
|---|-------------------------------------|
| Electrical: Power & Controls | |
| *2CV255 | 1 1/2HP, 115V, 1PH, 60 Hz |
| 2CV256 | 1 1/2HP, 230V, 1PH, 50 Hz |
| Pump | |
| *2CW266 | Pump/Plumbing For 60 Hz Electrical |
| 2CW267 | Pump/Plumbing For 50 Hz Electrical |
| Finish Options | |
| *2CW263 | No Cover |
| 2CV257 | Cover, Painted |
| 2CV258 | Cover, Stainless |
| Stationary Or Portable Options | |
| *2CV259 | Stationary |
| 2CW260 | Portability Kit, Casters |
| Discharge Options | |
| *2CW261 | No Soap Injection, 15' Hose |
| 2CW262 | Soap Injection, Discharge, 50' Hose |

NOTE: * reflects the standard



Quality Assured Firm
 ISO 9001 Certified

