



865 West 2600 South, Salt Lake City, UT 84119
 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com

G Hydroblaster™

(Gasoline Engine, Cold Water)

MODEL	3.5/3000G	5/3000	5/5000
VOLUME (GPM)	3.5	5	5
PRESSURE (PSI)	3000	3000	5000
WEIGHT (LBS)	190	280	297
GASOLINE ENGINE (HP)	11 Direct driven	20 Belt driven	25 Belt Driven
FUEL CAPACITY	1.8 gallons	8 gallons	8 gallons
MOUNTING	Formed steel base plate mounted, hose rack, gun holster, full cage protection and optional casters (2 rigid and 2 locking swivels).		
LENGTH (INCHES)	38		
WIDTH	18		
HEIGHT	27		

Hydroblaster not supplied with battery

Meets UL1776 Standards for Outdoor Applications

Standard Features

- General Pump
- Trigger gun with insulated variable pressure wand
- 50' high pressure hose
- Downstream chemical injection
- Formed metal skid with forklift slots

Engine: Power & Controls

- STD- 11HP, Pull Start (3.5/3000G)
- OPT- 11HP, Electric Start (3.5/3000G)
- STD- 20HP, Electric Start (5/3000G)
- STD- 25HP, Electric Start (5/5000G)

Engine: Battery Options

- STD- No Battery
- OPT- Battery, Liquid Acid, Non Shippable
- OPT- Battery, Spiral Cell, Shippable

Gauge & Meter Options

- STD- No Pressure Gauge
- OPT- Pressure Gauge
- STD- No Hour Meter
- OPT- Hour Meter

Skid Or Portable Mount Options

- STD- Skid Mount
- OPT- Portability Kit, Casters

Discharge Options

- STD- Single High Pressure Nozzle, 15 Degree
- OPT- Four Nozzle Kit, 0,15,25,40 Degree
- OPT- Turbo Nozzle
- OPT- Hose Reel Kit



Shown with optional portability kit (casters) and battery.



Quality Assured Firm

ISO 9001 Certified



Certified Systems Available