

Hydroblaster™ GS Series

MODEL	5/3000	10/2000	5/5000
VOLUME (GPM)	5	10	5
PRESSURE (PSI)	3000	2000	5000
GASOLINE ENGINE (HP)	18	25	25
FUEL CAPACITY	8 gallons		
LENGTH (INCHES)	56L X 30W X 32 ¼ H		
WEIGHT	660	795	750



Shown with options

**Standard Features:**

- UL1776, CSA & CE Certified
- Heavy channel iron skid with forklift slots
- Belt drive
- Full locking hinged equipment covers
- Trigger gun
- Insulated variable pressure wand
- 15 degree nozzle
- 50' hose rated 3000 PSI
- Downstream chemical injection

Part#	Description
	<b>Engine: Power &amp; Controls</b>
*1YM125	Kohler 18HP, Electric Start (5/3000 only)
2BL890	Honda 20HP, Electric Start (5/3000 only)
2FB838	Kohler 25HP, Electric Start
2FB839	Kubota Diesel, H2O Cooled, (available on all models)
	<b>Engine: Battery Options</b>
*1YG062	No Battery
1YG063	Battery, Liquid Acid, Non Shippable
1YG064	Battery, Spiral Cell, Shippable
	<b>Gauge &amp; Meter Options</b>
*2TH533	No Pressure Gauge
2EM683	Pressure Gauge, Panel Mt.5000 PSI,GS
*1SU640	No Hour Meter
1WR653	Hour Meter
	<b>GS Enclosure Options</b>
*2EF610	Painted Housing, Gas Engine
2EF611	Stainless Steel Housing, Gas Engine
2EF612	Painted Housing, Diesel Engine
2EF613	Stainless Steel Housing, Diesel Engine
	<b>Discharge Options</b>
*1XH816	Single High Pressure Nozzle, 15 Deg
1XH817	Four Nozzle Kit, 0,15,25,40 Deg
2FV035	Hose Reel Kit, 10 GPM & 3000 PSI, GS

NOTE: \* reflects the standard