

Hydro Heater – LP Gas Fired Heat

MODEL HH-LP

VOLUME (GPM)	2-4 GPM	5 GPM	6-7 GPM
WEIGHT (LBS)	220	285	
DIMENSIONS	20" W X 43" H X 21" L	21" W X 46" H X 21" L	

Standard Features:

- Can be used with most pressure washers
- Fuel – LP gas
- Requires 110 volt power supply
- Pressure controlled burner cycling
- Tough 11 gauge steel frame
- High pressure pop-off safety valve
- Over pressure rupture disc
- High limit temperature controls
- Gas regulator is not supplied

Choose your options (STD- designates the standard)

Temperature Controls

STD- Thermostat, 225' High Limit, NC

OPT- Thermostat, Adjustable, 85-250'F_

Electrical: Power & Controls

STD- 115 Volt, Auto Burner Ignition

Flow & Trim Options

STD- 2 GPM, To 4000 PSI, Painted Trim

OPT- 2 GPM, To 4000 PSI, Stainless Trim

OPT- 3-4 GPM, To 4000 PSI, Painted Trim

OPT- 3-4 GPM, To 4000 PSI, Stainless Trim

OPT- 5 GPM, To 4000 PSI, Painted Trim

OPT- 5 GPM, To 4000 PSI, Stainless Trim

OPT- 6-7 GPM, To 4000 PSI, Painted Trim

OPT- 6-7 GPM, To 4000 PSI, Stainless Trim

Exhaust Options

STD- Draft Diverter 8" Flue, Painted Top

OPT- Draft Diverter 8" Flue, Stainless Top

OPT- Draft Diverter, 10", Painted Top

OPT- Draft Diverter, 12" Painted Top

OPT- Power Vent System, 2-4 gpm

OPT- Power Vent System, 5 gpm

OPT- Power Vent System, 6-7gpm

System Gauge Options

STD-No Pressure Gauge

OPT-Pressure Gauge, Pipe Mounted

OPT-Temperature Gauge



865 West 2600 South, Salt Lake City, UT 84119
 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com