

Hydro Heater - Oil Fired Heat

MODEL HH-O

VOLUME (GPM)	2-4 GPM	5 GPM	6-7 GPM
WEIGHT (LBS)	220	285	
DIMENSIONS	20" W X 43" H X 21" L	21" W X 46" H X 21" L	

Standard Features:

- Can be used with most any pressure washer
- Fuel – Oil (#1-2 diesel, kerosene, stove oil, JP4 or JP8)
- Requires 110 volt power supply
- Pressure controlled burner cycling
- Tough 11 gauge steel frame
- High pressure pop-off safety valve
- Over pressure rupture disc
- High limit temperature controls
- Gas regulator is not supplied

Choose your options (STD- designates the standard)

Temperature Controls

STD- Thermostat, 225° High Limit, NC
OPT- Thermostat, Adjustable, 85-250°F

Electrical: Power & Controls

STD- 12 Volt DC, 2-4 GPM
OPT- 115 Volt, 2-4 GPM
OPT- 115 Volt, 2-4 GPM, Portable
OPT- 12 Volt DC, 5 GPM
OPT- 115 Volt, 5 GPM
OPT- 115 Volt, 5 GPM, Portable
OPT- 115 Volt, 6-7 GPM

Flow & Trim Options

STD- 2 GPM, To 4000 PSI, Painted Trim
OPT- 2 GPM, To 4000 PSI, Stainless Trim
OPT- 3-4 GPM, To 4000 PSI, Painted Trim
OPT- 3-4 GPM, To 4000 PSI, Stainless Trim
OPT- 5 GPM, To 4000 PSI, Painted Trim
OPT- 5 GPM, To 4000 PSI, Stainless Trim
OPT- 6-7 GPM, To 4000 PSI, Painted Trim
OPT- 6-7 GPM, To 4000 PSI, Stainless Trim

Exhaust Options

STD- Draft Diverter 8" Flue, Painted Top
OPT- Draft Diverter 8" Flue, Stainless Top
OPT- Draft Diverter, 10", Painted Top
OPT- Draft Diverter, 12" Painted Top
OPT- Power Vent System, 2-4 GPM
OPT- Power Vent System, 5 GPM
OPT- Power Vent System, 6-7 GPM



System Gauge Options

STD-No Pressure Gauge
OPT-Pressure Gauge, Pipe Mounted
OPT-Temperature Gauge

Frame Options

STD-Stationary, 18"
OPT-Stationary, 20"
OPT-Portability Tilt Back, 18"