### "Jumper Hose" **Machine To Reel**



- Connects Equipment to the Reel
- Rated to over 4400 PSI
- One Swivel End and One Fixed End

PART #	DESCRIPTION
1172	2'JUMPER HOSE WITH ENDS
1173	3'JUMPER HOSE WITH ENDS
1174	4' JUMPER HOSE WITH ENDS
1175	5'JUMPER HOSE WITH ENDS
1176	6'JUMPER HOSE WITH ENDS
1177	7'JUMPER HOSE WITH ENDS
1178	8'JUMPER HOSE WITH ENDS
1179	9'JUMPER HOSE WITH ENDS
1180	10'JUMPER HOSE WITH ENDS
1181	11'JUMPER HOSE WITH ENDS
1182	12'JUMPER HOSE WITH ENDS
1183	13'JUMPER HOSE WITH ENDS
1184	14'JUMPER HOSE WITH ENDS
1185	15'JUMPER HOSE WITH ENDS
1186	16' JUMPER HOSE WITH ENDS
1187	17' JUMPER HOSE WITH ENDS
1188	18' JUMPER HOSE WITH ENDS
1189	19' JUMPER HOSE WITH ENDS
1190	20'JUMPER HOSE WITH ENDS

# **Re-Usable**

Excellent for field repairs & temporary fixes of high pressure hose.





No special tools are required.

PART#	DESCRIPTION
1191	1 WIRE, 3/8", FIXED
1192	1 WIRE, 3/8", SWIVEL
1193	2 WIRE, 3/8", FIXED
1194	2 WIRE, 3/8", SWIVEL

#### **SERPENTINE PRESSURE WASH HOSE**

THE INDUSTRY'S #1 SELLING HOSE!

OUR 4.5 & 6.000 HOSES WORK HARDER & WEIGH LESS THAN THEIR 3,000, 4,500 & 5800 PSI

## AND LASTS MUCH LONGER!

- Super tough cover design
- 1 ea. 3/8" MPT swivel end
- 1 ea. 3/8" MPT fixed end
- Temperature to 250°F
- Tough wrapped outer cover
- Strain reliefs on both ends

Longer Lengths Available by Calling 1-800-346-4876

4,000 PSI 50' BLACK 3/8" #1708 1 WIRE

4.000 PSI 100' BLACK 3/8" #1709 1 WIRE

4,000 PSI **50' GREY** 3/8" #1804 1 WIRE

4,000 PSI 100' GREY 3/8" #1805 1 WIRE

5,000 PSI 50' BLACK 3/8" #1718 2 WIRE

5,000 PSI 100' BLACK 3/8" #1719 2 WIRE

6,000 PSI

5,000 PSI 50' GREY 3/8" #1806 2 WIRE

5,000 PSI 100' GREY 3/8" #1807

2 WIRE

6,000 PSI 50' BLACK 3/8" #6001 2 WIRE

1/2"

3,000 PSI

50' BLACK

#1700

1 WIRE

100' BLACK 3/8" #6002 2 WIRE

6,000 PSI **50' GREY** 3/8" #6101 2 WIRE

6,000 PSI 100' GREY 3/8" #6102 2 WIRE

1/2" 3.000 PSI 100' BLACK #1701 1 WIRE

1/2" 4,500 PSI 50' BLACK #1710 2 WIRE

1/2" 4,500 PSI **100' BLACK** #1711 2 WIRE



## **Premium Hose Reel Hose** & Tank to Equipment Hose

FIGURE 'A' is what a healthy, non-collapsing hose looks like. The advantages are: When on a hose reel the first few layers will not 'mash down' and restrict the flow of water from the source to you supply tank. Also, when you use this hose to feed water from the supply tank to the machine the heat will not make this hose become 'spongy' and restrict water flow.

FIGURE 'B' is what is found on 95% of all the hose reels in the country. It too is a premium grade industrial water hose that is 50 times the quality of the typical water hose you will find in a 'high end' hardware store. This is the same hose I had to live with for 15 years as a Mobile Washer and it was not fun. It took forever to fill my supply tank for obvious reasons.

PART #	DESCRIPTION
3415	150' with Crimped GH Connector & Strain Relief. Other end open.
3420	300' with Crimped GH Connector & Strain Relief. Other end open.



Comes with 'crimped on' faucet connector with 'strain relief.' The other end is open so it will attach to a barb on the reel.