Allison Severe Duty Performance Pumps



Allison Severe Duty Pumps will run harder & last longer than any pump in the industry and to show you just how confident we are that our Severe Duty pumps are better all you have to do is look at this warranty.

- 'Everything included' warranty for 2 years on Severe Duty Pumps.
- 10 Year Warranty on Head and Crank Shaft on Severe Duty Pumps
- 10 Year Warranty on Bearings and Connecting Rods on Severe Duty Pumps
- Larger Bearings for greater belt'side-loads' means longer pump back-end life.
- Turned & Balanced Connecting Rods for the smoothest run in the industry.
- 'State of the Art' Packing Design means longer, uninterrupted run-times.
- Cool-run Technology through Extra Capacity Oil Sumps reduces pump wear.

Model	GPM	PSI	RPM	Drive	Gas HP	Weight	LIST PRICE	CONTRACTOR
SD5645	5.6	4500	1450	24mm	23	40	\$1650.00	\$
SD8036	8.0	3600	1450	24mm	28	45	\$1775.00	\$
SD1030	10.0	3000	1450	24mm	28	45	\$1840.00	\$

The SD5645 is a direct replacement for the TS2021 with a much higher PSI rating, longer life span and Bumper to Bumper 2-Year Warranty.

THE ONLY PUMP in the World with a

2-YEAR **BUMPER-TO-BUMPER** WARRANTY

that covers Valves, Packings, Seals and everything else including Labor!

JUST HOW GOOD IS AN

Allison

Severe Duty Performance Pump?

EnviroSpec will provide a full 2-year warranty on Allison Severe Duty Pumps purchased individually or any Allison Severe Duty Pump that is installed on a machine that we manufacture. This warranty covers virtually every component on the pump including 'high wear items' such as check valves, packings & oil seals.

EnviroSpec also provides a free oil change & 42-Point Inspection on the anniversary dates for the first two years. Simply call for an RGA, return the pump to us prepaid and a certified systems technicial will take over from there.

Our job and promise is to keep your equipment running with little to no down time and we do that by providing our customers with a certified pump inspection and service program that you can't get anvwhere else.

5,000 **PSI HOSE REEL SWIVEL**

- FPT x FPT
- 3/8" FPT inlet for hose
- 1/2" outlet mounts to reel



· Rugged carbon steel construction

- Blow-out proof stem
- Delrin® ball seats
- Buna-N® o'rings

