MATERIAL SAFETY DATA SHEET OSHA - Meets 29 CFR 1910.1200 Standards HMIS HAZARD RATINGS **HEALTH** = Chronic Health Hazard 2 = MODERATE 1 Soap For Hope **FLAMMABILITY** 0 0 = INSIGNIFICANT 3 = HIGH0 PHYSICAL HAZARD 1 = SLIGHT 4 = EXTREME TRANSPORTATION INFORMATION PROPER SHIPPING NAME: Not Regulated Over 60% of the profits derived from the manufacturing of **EnviroSpec Cleaning Chemicals** HAZARD CLASS / PKG GRP: Not regulated REF: Not Applicable **IDENTIFICATION NUMBER:** None LABEL: None Required SECTION 1 - PRODUCT / COMPANY IDENTIFICATION IDENTITY (AS USED ON LABEL AND LIST) Page 1 of 2 **ZPBONP** MANUFACTURER'S NAME **EMERGENCY TELEPHONE NUMBER** Chemtrec (800) 424-9300 Outside USA (703) 527-3887 EnviroSpec ADDRESS (NUMBER, STREET, P.O. BOX) TELEPHONE NUMBER FOR INFORMATION 751 MLK Highway (912) 487-1778 (CITY, STATE AND ZIP CODE) DATE PREPARED: April 11, 2005 Homerville, GA 31634 SUPERSEDES: New SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION HAZARDOUS COMPONENTS **OSHA PEL ACGIH TWA** SARA RQ CAS# TITLE III (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S)) (OPTIONAL) PPM MG/M3 PPM MG/M3 LBS Sodium phosphate, tribasic (STPP) (a) 7758-29-4 30 - 60not established 5000 NTA Trisodium salt, monohydrate (b,c,d) 18662-53-8 10 - 30not established 111-76-2 3 - 7 50 20 Ethylene glycol monobutyl ether (e,f) 240 Yes (a) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 10,000 lbs) or greater amounts, according to 40 CFR 302. (b) NTA Trisodium salt, monohydrate is not listed on the Canadian DSL or NDSL because it is a hydrate. The CAS number for the anhydrous form is on the list. All other components of this product identified by CAS number are listed on the DSL or NDSL. (c) Indicates substance appears on National Toxicology Program (NTP) list of carcinogens, International Agency for Research on Cancer (IARC) list of carcinogens or is regulated by the Occupational Safety and Health Administration (OSHA) as a possible carcinogen. (d) California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986, chemicals known to the state to cause cancer or reproductive toxicity. A person in the course of doing business must warn others who may consume, come into contact with, or otherwise be exposed to this chemical. (e) A "Yes" in the SARA TITLE III column in Section 2 indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. (f) Indicates an employee's skin exposure shall be prevented or reduced to the extent necessary in the circumstances through the use of gloves, coveralls, goggles, or other appropriate equipment. SECTION 3 - HEALTH HAZARD DATA ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE **EMERGENCY AND FIRST AID PROCEDURES** INHALATION: Breathing dusts may cause irritation of respiratory tract. Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention. SKIN: Prolonged contact may cause irritation. Wash contacted area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention. EYES: Contact with eyes will cause irritation. Check for and remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention INGESTION: May cause gastric distress, vomiting and diarrhea. Drink large quantities of water or milk; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention immediately CARCINOGENICITY Yes Yes NTP? IARC MONOGRAPHS? OSHA REGULATED? NTA Trisodium salt, monohydrate appears on National Toxicology Program (NTP) list of carcinogens, International Agency for Research on Cancer (IARC) list of carcinogens or is regulated by the Occupational Safety and Health Administration (OSHA) as a possible carcinogen. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through

prolonged exposure.

MATERIAL SAFETY DATA SHEET IDENTITY (AS USED ON LABEL AND LIST) Page 2 of 2 **ZPBONP** Date: April 11, 2005 SECTION 4 - FIRE FIGHTING MEASURES FLASH POINT (METHOD USED) NFPA RATING FLAMMABLE LIMITS Non-flammable None LEL: Not applicable UEL: Not applicable **EXTINGUISHING MEDIA** Carbon dioxide, water, water fog, dry chemical, chemical foam. SPECIAL FIRE FIGHTING PROCEDURES Floor will become slippery if material is released and mixed with water. Material is alkaline and will irritate the eyes if product is allowed to directly contact the UNUSUAL FIRE AND EXPLOSION HAZARDS SECTION 5 - ACCIDENTAL RELEASE MEASURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Material is alkaline and will irritate the eyes if product is allowed to directly contact the eyes. Wash small spills to sanitary sewer. Large spills - confine spill, shovel product into approved container for disposal. For spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313. 40 CFR 372 concerning reporting requirements. SECTION 6 - HANDLING AND STORAGE PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Store in cool, dry area. Keep this and other chemicals out of reach of children. SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations. VENTILATION LOCAL EXHAUST: SPECIAL: To maintain minimum TWA and STEL levels. Required MECHANICAL (GENERAL): OTHER: Engineering and work controls as required. PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs. EYE PROTECTION: Chemical safety goggles OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls, apron, or other equipment should be worn to prevent skin contact, safety eyewash station near WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general. SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES **BOILING POINT** SPECIFIC GRAVITY (WATER = 1) Not applicable 2.5 - 2.8VAPOR PRESSURE (MM Hg) Not applicable 11.5 - 12.5 (2% aqueous solution) VAPOR DENSITY (AIR = 1) **EVAPORATION RATE (WATER = 1)** Not applicable Not applicable % VOLATILE (BY WEIGHT) **SOLUBILITY IN WATER** Complete < 7% APPEARANCE AND ODOR White free flowing powder, characteristic odor SECTION 9 - STABILITY AND REACTIVITY **STABILITY** UNSTABLE: CONDITIONS TO AVOID: Avoid generating airborne dust. STABLE: XXX INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids, strong alkalies. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced. CONDITIONS TO AVOID: None HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for alkaline materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.